

Package ‘datana’

June 5, 2025

Title Datasets and Functions to Accompany Analisis De Datos Con R

Version 1.0.9

Description Datasets and functions to accompany the book 'Analisis de datos con el programa estadístico R: una introducción aplicada' by Salas-Eljatib (2021, ISBN: 9789566086109).
The package helps carry out data management, exploratory analyses, and model fitting.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 3.5)

LazyData true

LazyDataCompression xz

Imports ggplot2, Hmisc, methods, stats, utils

Suggests lattice

NeedsCompilation no

Author Christian Salas-Eljatib [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-8468-0829>>),
Campos Nicolás [ctb] (ORCID: <<https://orcid.org/0009-0001-9534-9808>>),
Pino Nicolas [ctb] (up to 2020),
Riquelme Joaquin [ctb] (up to 2020)

Maintainer Christian Salas-Eljatib <cse1jatib@gmail.com>

Repository CRAN

Date/Publication 2025-06-05 19:30:02 UTC

Contents

aboutrsq	4
aboutrsq2	5
airnyc	6
airnyc2	7
annualppCities	8
annualppCities2	8

bears	9
bears2	10
bearsdepu	11
bearsdepu2	12
beetles	13
beetles2	14
cameratrapp	15
cameratrapp2	16
carAccidents	17
casen	18
cdf	19
chicksw	20
chicksw2	21
co2temp	21
contrast	24
corkoak	26
corkoak2	27
deleteLeft	28
deleteRight	29
descstat	30
election	31
election2	31
eucaleaf	32
eucaleaf2	33
eucaleafAll	34
eucaleafAll2	35
extractLeft	36
extractRight	37
fertiliza	38
fertiliza2	38
ficdiamgr	39
ficdiamgr2	40
findColumn.byname	41
fishgrowth	42
fishgrowth2	43
forestfire	43
forestfire2	45
gdpcap	46
gmean	47
hgrdfir	48
hgrdfir2	49
hmean	50
idahohd	51
idahohd2	52
kurto	53
landcover	54
landcover2	55
largetrees	56

largetrees2	57
lifexpect	58
llancahue	59
llancahue2	60
lrt	61
lrt.glm	62
moda	63
papersdocstu	64
presenceIce	65
president	66
primarias	67
pspLlancahue	68
pspruca	69
pspruca2	70
ptaeda	71
ptaeda2	71
pvalt	72
pvalz	73
rainfallCA	74
raulhg	75
raulhg2	76
skew	77
sludge	78
sludge2	78
snaspe	79
snaspe2	80
soiltreat	81
soiltreat2	82
spataustria	83
tabtexdescstat	84
timeserplot	85
treevol	88
treevol2	89
treevolroble	89
treevolroble2	90
xyboxplot	91
xyhist	93
xymultiplot	94

aboutrsq

About the R-Squared statistics: the Anscombe quartet dataset

Description

A dataset that contains four pairs of columns with the same descriptive statistics; however, there is a difference when representing the points through a graph.

Usage

```
data(aboutrsq)
```

Format

The data frame contains four variables as follows:

X1 Integers values that represent X-axis for Y1, Y2 and Y3 column

Y1 Float values that represent Y-axis for X1 column

Y2 Float values that represent Y-axis for X1 column

Y3 Float values that represent Y-axis for X1 column

X2 Integers values that represent X-axis for Y4 column

Y4 Float values that represent Y-axis for X2 column

Source

Data were assembled by Dr Christian Salas-Eljatib (Santiago, Chile).

References

Anscombe FJ. 1973. Graphs in statistical analysis. The American Statistician 27:17-21. doi:[10.2307/2682899](https://doi.org/10.2307/2682899)

Examples

```
data(aboutrsq)
head(aboutrsq)
```

aboutrsq2*Sobre el estadístico R2: los datos del cuarteto de Anscombe*

Description

Dataset que contiene cuatro pares de columnas con la mismos estadísticos descriptivos, sin embargo, si existe diferencia al representar los puntos mediante un gráfico.

Usage

```
data(aboutrsq2)
```

Format

Variables se describen a continuación::

X1 Valores enteros que representan el eje X para las columnas Y1, Y2 e Y3

Y1 Valores flotantes que representan el eje Y para la columna X1

Y2 Valores flotantes que representan el eje Y para la columna X1

Y3 Valores flotantes que representan el eje Y para la columna X1

X2 Valores enteros que representan el eje X para las columnas Y4

Y4 Valores flotantes que representan el eje Y para la columna X2

Source

Datos fueron contribuidos por el Prof. Christian Salas-Eljatib (Universidad de Chile, Santiago, Chile).

References

Anscombe FJ. 1973. Graphs in statistical analysis. The American Statistician 27:17-21. doi:[10.2307/2682899](https://doi.org/10.2307/2682899)

Examples

```
data(aboutrsq2)
head(aboutrsq2)
```

`airnyc`*Airquality data in New York city.*

Description

Daily air quality measurements in New York, May to September 1973.

Usage

```
data(airnyc)
```

Format

Contains 6 variables, as follows:

ozone numeric Ozone (ppb).

solar numeric Solar R (lang).

wind numeric Wind (mph).

temp numeric Temperature (degrees F).

month numeric Month (1–12).

day numeric Day of month (1–31).

Source

The data were obtained from the library *datasets*.

References

Chambers J, Cleveland W, Kleiner B, Tukey P. 1983. Graphical Methods for Data Analysis. Belmont, CA: Wadsworth.

Examples

```
data(airnyc)
head(airnyc)
```

`airnyc2`*Calidad del aire en la ciudad de Nueva York.*

Description

Calidad del aire diario medido en New York, de Mayo a Septiembre de 1973.

Usage

```
data(airnyc2)
```

Format

Contiene 6 variables:

ozone Ozono (ppb).

solar Solar R (largo).

wind Viento (mph).

temp Temperatura (grados F).

month Mes del año (1–12).

day Dia del mes (1–31).

Source

Los datos fueron obtenidos desde la librería 'datasets'.

References

Chambers J, Cleveland W, Kleiner B, Tukey P. 1983. Graphical Methods for Data Analysis. Belmont. CA: Wadsworth.

Examples

```
data(airnyc2)
head(airnyc2)
```

annualppCities	<i>Time series of annual precipitations in cities of Chile.</i>
----------------	---

Description

Data contains annual precipitations in six cities in Chile (Santiago, Talca, Chillán, Temuco, Valdivia, and Puerto Montt) at different years.

Usage

```
data(annualppCities)
```

Format

The dataframe contains three variables as follows:

city Name of city.

year Year of registry.

annual Value of the annual precipitation of a given year (mm).

Source

The data were obtained from <https://explorador.cr2.cl/>.

Examples

```
data(annualppCities)
head(annualppCities)
```

annualppCities2	<i>Serie de tiempo de precipitaciones anuales en Chile.</i>
-----------------	---

Description

Data contains annual precipitations in six cities in Chile (Santiago, Talca, Chillan, Temuco, Valdivia, and Puerto Montt) at different years.

Usage

```
data(annualppCities2)
```

Format

The dataframe contains three variables as follows:

ciudad Name of city.

anho Year of registry.

pp.anual Value of the annual precipitation of a given year (mm).

Source

Los datos fueron obtenidos desde <https://explorador.cr2.cl/>.

Examples

```
data(annualppCities2)
head(annualppCities2)
```

bears	<i>Age and physical measurement data for wild bears</i>
-------	---

Description

Wild bears were anesthetized, and their bodies were measured and weighed. One goal of the study was to make a table (or perhaps a set of tables) for people interested in estimating the weight of a bear based on other measurements. Notice that there are missing values for some of the variables.

Usage

```
data(bears)
```

Format

Contains individual-level variables, as follows:

id Bear id
age Age in total number of months.
month Month number within a given year.
sex 1 =male, 2 = female.
headL Length of head, in cm.
headW Width of head, in cm.
neckG Girth of neck, in cm.
length Body length, in cm.
chestG Girth of chest, in cm.
weight body weight, in kg.
obs Temporal observation number for bear.
name Name given to bear.

Source

According to Prof. Timothy Gregoire at Yale University (New Haven, CT, USA), the data set was supplied by Gary Alt.

References

Entertaining references are in Reader's Digest April, 1979, and Sports Afield September, 1981.

Examples

```
data(bears)
head(bears)
table(bears$sex)
boxplot(headL~sex, data=bears)
```

bears2

Edad y características biométricas de osos salvajes

Description

Los osos salvajes fueron anestesiados y sus cuerpos medidos. Uno de los objetivos del estudio fue hacer una tabla (o quizás un conjunto de tablas) para las personas interesadas en estimar el peso de un oso basandose en otras medidas. Observe que faltan valores para algunas de las variables.

Usage

```
data(bears2)
```

Format

Contiene variables de nivel individual, como se describen a continuación:

id Identificador del oso.

edad edad en meses

mes identificador del mes,dentro del año.

sexo 1 = macho, 2 = hembra

cabezaL longitud de la cabeza, en cm

cabezaA ancho de la cabeza, en cm

cuelloP circunferencia del cuello, en cm

largo longitud del cuerpo, en cm

pechoG circunferencia del pecho, en cm

peso peso corporal, en kg

obs número de observación temporal para el oso

nombre nombre dado al oso

Source

Segun el Prof. Timothy Gregoire de Yale University (New Haven, CT, USA), los datos fueron cedidos por Gary Alt. Minitab, Inc. La descripcion de los datos fue dada por él.

References

Algunas referencias generales estan en el Reader's Digest de Abril, 1979, y Sports Afield de Septiembre, 1981.

Examples

```
data(bears2)
head(bears2)
table(bears2$sexo)
boxplot(cabezaL~sexo, data=bears2)
```

bearsdepu	<i>Age and physical measurement data for wild bears (without missing values)</i>
-----------	--

Description

Wild bears were anesthetized, and their bodies were measured and weighed. One goal of the study was to make a table (or perhaps a set of tables) for people interested in estimating the weight of a bear based on other measurements.

Usage

```
data(bearsdepu)
```

Format

Individual-level variables, as follows:

id Bear identifier.
age Age in total number of months.
month Month number within a given year.
sex Sex code: 1 =male, 2 = female.
headL Length of head, in cm.
headW Width of head, in cm.
neckG Girth of neck, in cm.
length Body length, in cm.
chestG Girth of chest, in cm.
weight Body weight, in kg.
obs Temporal observation number for bear.
name name given to bear

Source

According to Prof. Timothy Gregoire at Yale University (New Haven, CT, USA), the data set was supplied by Gary Alt.

References

Entertaining references are in Reader's Digest April, 1979, and Sports Afield September, 1981.

Examples

```
data(bearsdepu)
head(bearsdepu)
table(bearsdepu$sex)
boxplot(headL~sex, data=bearsdepu)
```

bearsdepu2	<i>Edad y características biométricas de osos salvajes (sin datos faltantes)</i>
------------	--

Description

Los osos salvajes fueron anestesiados y sus cuerpos medidos. Uno de los objetivos del estudio fue hacer una tabla (o quizás un conjunto de tablas) para las personas interesadas en estimar el peso de un oso basandose en otras medidas. Esta dataframe es igual que "bears" pero sin valores perdidos.

Usage

```
data(bearsdepu2)
```

Format

Contiene variables de nivel individual, como se describen a continuacion:

id Identificador del oso.
edad edad en meses.
mes identificador del mes,dentro del año.
sexo 1 = macho, 2 = hembra.
cabezaL longitud de la cabeza, en cm.
cabezaA ancho de la cabeza, en cm.
cuelloP circunferencia del cuello, en cm.
largo longitud del cuerpo, en cm.
pechoG circunferencia del pecho, en cm.
peso peso corporal, en kg.
obs número de observación temporal para el oso.
nombre nombre dado al oso.

Source

Segun el Prof. Timothy Gregoire de Yale University (New Haven, CT, USA), los datos fueron cedidos por Gary Alt. Minitab, Inc. La descripcion de los datos fue dada por él.

References

Algunas referencias generales estan en el Reader's Digest de Abril, 1979, y Sports Afield de Septiembre, 1981.

Examples

```
data(bearsdepu2)
head(bearsdepu2)
table(bearsdepu2$sexo)
boxplot(cabezaL~sexo, data=bearsdepu2)
```

beetles

Population density growth of beetles

Description

Temporal measurements of density of beetles (*Tribolium confusum*) growing in different controlled environments.

Usage

```
beetles
```

Format

days Number of days.

diet The quantities of flour (in grams) of the environments where the beetles were growing. Six levels of the factor Diet.

type The various stage of beetles, i.e., eggs, larvae, pupae, and adults.

density The number of insects per environment.

Source

Data from Table No. 1, page 116, of Chapman (1928). Series of experiments under controlled conditions in which flour beetles (*Tribolium confusum*) are kept in environments of known size. The period from egg to adult is approximately forty days at 27C degrees. The data were entered by Miss Yamara Arancibia, a former student of Prof. Christian Salas-Eljatib.

References

- Chapman RN. 1928. The quantitative analysis of environmental factors. Ecology 9(2):111-122. [doi:10.2307/1929348](https://doi.org/10.2307/1929348)

Examples

```
data(beetles)
table(beetles$type)
name.diet<-unique(beetles$diet)
num.diet<-length(name.diet)
##Time series plot
#first, some computation
alys<-with(beetles,tapply(density,list(as.factor(days),as.factor(diet)),sum))
out<-as.data.frame(alys)
out$time<-row.names(out)
head(out)
#Figure 1 of the paper
matplot(out[, "time"], out[, 1:num.diet], las=1, type=c("b"),pch=1,
        xlab="Time in days",ylab="Total individuals")
legend("topleft", legend = name.diet, title = "Diet (gr)",
       col = 1:6, lty = 1:6, pch = 1)
```

beetles2

Crecimiento poblacional de escarabajos

Description

Mediciones temporales de densidad de escarabajos (*Tribolium confusum*) creciendo en diferentes ambientes controlados.

Usage

```
beetles2
```

Format

dias Número de días.

dieta La cantidad de harina (en gramos) de ambientes donde crecen los escarabajos. Seis niveles del factor Dieta.

tipo Estados de desarrollo de los escarabajos, i.e., huevos, larvas, pupas, y adultos.

densidad Número total de individuos por ambiente de crecimiento.

Source

Datos del Cuadro No. 1, page 116, de Chapman (1928). Serie de experimentos bajo condiciones controladas donde escarabajos (*Tribolium confusum*) se mantienen en ambientes de tamaño conocido. El periodo desde huevo a adulto es de aproximadamente de cuarenta días a 27 grados Celsius. Los datos fueron digitados por la Srta. Yamara Arancibia, una estudiante del Prof. Christian Salas-Eljatib.

References

- Chapman RN. 1928. The quantitative analysis of environmental factors. Ecology 9(2):111-122. doi:10.2307/1929348

Examples

```
data(beetles2)
table(beetles2$tipo)
nom.dieta<-unique(beetles2$dieta)
num.dieta<-length(nom.dieta)
##Grafico de serie de tiempo
#primero algunos calculos
alys<-with(beetles2,tapply(
  densidad,list(as.factor(dias),as.factor(dieta)),sum)
)
out<-as.data.frame(alys)
out$tiempo<-row.names(out)
head(out)
##Figura 1 del paper
matplot(out[, "tiempo"], out[,1:num.dieta], las=1, type=c("b"),pch=1,
  xlab="Tiempo en dias",ylab="Densidad de individuos")
legend("topleft", legend = nom.dieta, title = "Dieta (gr)",
  col = 1:6, lty = 1:6, pch = 1)
```

cameratrapp

Camera trap data on mammals in Ruaha National Park, southern Tanzania.

Description

Dataset contains 14604 observations and sampling was carried out for two months during the dry season of 2013 and two months during the wet season of 2014. Each camera station is associated with a randomly placed camera and a trail-based camera, with the aim of comparing communities resulting from the two camera trap placement strategies.

Usage

```
data(cameratrapp)
```

Format

Contains 6 variables, as follows:

- reference** Number of observation of datasets.
- placement** Type of "placement" placed in each station (random or trail).
- season** Season where were made the samplings.
- station** Station where were collected the data.
- specie** Name of specie medium to large terrestrial mammals.
- date.time** The date and time of each photographic event is also given.

Source

The data were provided by Dr Jeremy Cusack.

References

- Cusack J, Dickman A, Rowcliffe M, Carbone C, Macdonald D, Coulson T. 2016. Random versus game trail-based camera trap placement strategy for monitoring terrestrial mammal communities. PLoS ONE 10(5): e0126373.

Examples

```
data(cameratrapp)
head(cameratrapp)
```

cameratrapp2	<i>Camaras trampa de mamiferos en el parque nacional Ruaha, en el sur de Tanzania</i>
--------------	---

Description

Contains information of Camera trap data on medium to large terrestrial mammals collected at 54 camera stations in Ruaha National Park, southern Tanzania. Dataset contains 14604 observations and sampling was carried out for two months during the dry season of 2013 and two months during the wet season of 2014. Each camera station is associated with a randomly placed camera and a trail-based camera, with the aim of comparing communities resulting from the two camera trap placement strategies.

Usage

```
data(cameratrapp2)
```

Format

Contiene 6 variables, como sigue:

referencia Number of observation of datasets.

posicion Type of "placement" placed in each station (random or trail).

temporada Season where were made the samplings.

estacion Station where were collected the data.

especie Name of specie medium to large terrestrial mammals.

fecha.hora The date and time of each photographic event is also given.

Source

Los datos fueron cedidos por el Dr Jeremy Cusack.

References

- Cusack J, Dickman A, Rowcliffe M, Carbone C, Macdonald D, Coulson T.
1. Random versus game trail-based camera trap placement strategy for monitoring terrestrial mammal communities. PLoS ONE 10(5): e0126373.

Examples

```
data(cameratrap2)
head(cameratrap2)
```

carAccidents	<i>Driver status after car accidents in Greece.</i>
--------------	---

Description

A data frame showing the use of seat belt and the driver status after a car accident in Greece.

Usage

```
data(carAccidents)
```

Format

Contains the factor variables:

record factor representing the driver status.

seatBelt factor indicating whether the driver wore a setbelt.

Source

R package 'gginference'

Examples

```
data(carAccidents)
head(carAccidents)
table(carAccidents)
```

casen

*Datos encuesta CASEN del 2022***Description**

Encuesta de Caracterización Socioeconómica Nacional (CASEN) de Chile, es realizada por el Ministerio de Desarrollo Social y Familia con el objetivo de disponer de información que permita conocer situación de los hogares y de la población. Estos datos corresponden a los de la encuesta CASEN 2022.

Usage

```
data(casen)
```

Format

Este set de datos contiene las siguientes columnas:

id.vivienda Identificador de la vivienda.

id.persona Identificador de la persona.

region Región administrativa de Chile.

comuna Comuna.

edad Edad de la persona, en años.

sexo Sexo de la persona.

esc Años de escolaridad (edad $\geq$ 15).

educ Clasificación de educación recibida.

personas.hogar Número de personas que habitan en el hogar.

tipohogar Nivel de tipo de hogar según encuesta.

activ Nivel de actividad actual de la persona según encuesta.

ytot Ingreso total.

ytoth Ingreso total del hogar.

ypch Ingreso total per cápita del hogar.

ytotcor Ingreso total corregido.

ytotcorh Ingreso total corregido del hogar.

ypc Ingreso total corregido per cápita del hogar.

mayor.nivel.edu ¿Cuál es el nivel educacional al que asiste o el más alto al cual asistió?

area.edu.cinef Clasificación Internacional Normalizada de Educación (CINE-F).

subarea.edu.cinef Clasificación Internacional Normalizada de Sub-Area de Educación (CINE-F).

previ.salud Sistema de previsión de salud.

Source

Los datos fueron obtenidos desde el web <https://observatorio.ministeriodesarrollosocial.gob.cl/encuesta-casen>. Note que solo algunas columnas son utilizadas aca, así como el nombre de algunas columnas fueron levemente cambiados.

Examples

```
data(casen)
head(casen)
table(casen$region)
table(casen$region,casen$sexo)
tapply(casen$ytotcor,casen$sexo,sum)
```

cdf

*Function to compute the cumulative distribution of a variable***Description**

Builds the cumulative distribution of a vector, using a step% of the data as fixed-intervals.

Usage

```
cdf(y = y, step = 0.05)
```

Arguments

y	a vector of a random variable
step	a numeric proportion of the data used as increment interval for building the cdf of the random variable. The default value for 'step' is 0.05, representing a 5%.

Details

By default the cumulative distribution is build using 5% of the data as intervals, that is to say, from 0.05 (i.e., 5%) to 0.95 (i.e., 95%).

Value

returns a dataframe having two columns: the first contains the random variable values and the second the cumulative distribution for the variable.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
y.var <- rnorm(10)
cdf(y.var)
cdf(y.var, step=0.1)
```

chicksw

Chicken growth data.

Description

The body weights of the chicks were measured at birth and every second day thereafter until day 20. They were also measured on day 21. There were four groups on chicks on different protein diets.

Usage

```
data(chicksw)
```

Format

Contains four variables, as follows:

chick An ordered factor with levels different giving a unique identifier for the chick. The ordering of the levels groups chicks on the same diet together and orders them according to their final weight (lightest to heaviest) within diet.

diet A factor with levels 1,2,3 and 4 indicating which experimental diet the chick received.

time A numeric vector giving the number of days since birth when the measurement was made.

weight A numeric vector giving the body weight of the chick (gm).

Source

The data were obtained from the *alr4* library.

References

Crowder M, Hand D. 1990. Analysis of Repeated Measures. Chapman and Hall

Examples

```
data(chicksw)
head(chicksw)
```

chicksw2*Crecimiento de pollos.*

Description

El peso de pollos fueron medidos al momento de nacer y cada día por medio hasta el día 20. Ellos también fueron medidos el día 21. Hubo cuatro grupos de pollos en diferentes dietas de proteínas.

Usage

```
data(chicksw2)
```

Format

Contiene cuatro variables, como sigue:

pollo Un identificador único para cada pollo. La numeración está ordenada según el peso final dentro de cada dieta.

dieta Un factor con cuatro niveles: 1,2,3 y 4 indicando qué dieta recibió el pollo.

tiempo Número de días desde el nacimiento.

peso Peso del pollo (gm).

Source

Los datos fueron obtenidos desde la librería *alr4*.

References

Crowder M, Hand D. 1990. Analysis of Repeated Measures. Chapman and Hall

Examples

```
data(chicksw2)
head(chicksw2)
```

co2temp*CO2 emissions and temperature at country-level.*

Description

Data obtained from the *hockeystick* package, which retrieves annual global carbon dioxide emissions since 1750 from the World Data repository <https://github.com/owid/co2-data>, as well as other climate-related variables.

Usage

```
data(co2temp)
```

Format

The data contains 75 variables, and the fully description can be reviewed in the references provided [here](#).

country Country.

year Calendar year.

iso_code TBA.

population Population size, in number of people.

gdp Gross domestic product, a measure of the value added created through the production of goods and services in a country.

cement_co2 TBA.

cement_co2_per_capita TBA.

co2 TBA.

co2_growth_abs TBA.

co2_growth_prc TBA.

co2_including_luc TBA.

co2_including_luc_growth_abs TBA.

co2_including_luc_growth_prc TBA.

co2_including_luc_per_capita TBA.

co2_including_luc_per_gdp TBA.

co2_including_luc_per_unit_energy TBA.

co2_per_capita TBA.

co2_per_gdp TBA.

co2_per_unit_energy TBA.

coal_co2 TBA.

coal_co2_per_capita TBA.

consumption_co2 TBA.

consumption_co2_per_capita TBA.

consumption_co2_per_gdp TBA.

cumulative_cement_co2 TBA.

cumulative_co2 TBA.

cumulative_co2_including_luc TBA.

cumulative_coal_co2 TBA.

cumulative_flaring_co2 TBA.

cumulative_gas_co2 TBA.

cumulative_luc_co2 TBA.
cumulative_oil_co2 TBA.
cumulative_other_co2 TBA.
energy_per_capita TBA.
energy_per_gdp TBA.
flaring_co2 TBA.
flaring_co2_per_capita TBA.
gas_co2 TBA.
gas_co2_per_capita TBA.
ghg_excluding_lucf_per_capita TBA.
ghg_per_capita TBA.
land_use_change_co2 TBA.
land_use_change_co2_per_capita TBA.
methane TBA.
methane_per_capita TBA.
nitrous_oxide TBA.
nitrous_oxide_per_capita TBA.
oil_co2 TBA.
oil_co2_per_capita TBA.
primary_energy_consumption TBA.
share_global_cement_co2 TBA.
share_global_co2 TBA.
share_global_co2_including_luc TBA.
share_global_coal_co2 TBA.
share_global_cumulative_cement_co2 TBA.
share_global_cumulative_co2 TBA.
share_global_cumulative_co2_including_luc TBA.
share_global_cumulative_coal_co2 TBA.
share_global_cumulative_flaring_co2 TBA.
share_global_cumulative_gas_co2 TBA.
share_global_cumulative_luc_co2 TBA.
share_global_cumulative_oil_co2 TBA.
share_global_cumulative_other_co2 TBA.
share_global_flaring_co2 TBA.
share_global_gas_co2 TBA.
share_global_luc_co2 TBA.
share_global_oil_co2 TBA.

```

share_global_other_co2 TBA.
share_of_temperature_change_from_ghg TBA.
temperature_change_from_ch4 TBA.
temperature_change_from_co2 TBA.
temperature_change_from_ghg TBA.
temperature_change_from_n2o TBA.
total_ghg TBA.
total_ghg_excluding_lucf TBA.
trade_co2 TBA.
trade_co2_share TBA.

```

Source

The data were obtained from the *hockeystick* library of R. Notice that in the dataframe only a portion of countries have been kept.

References

- <https://www.globalcarbonproject.org/carbonbudget/>
- Friedlingstein P. et al. 2020. Global Carbon Budget 2020, Earth System Science Data 12:3269-3340 [doi:10.5194/essd1232692020](https://doi.org/10.5194/essd1232692020)

Examples

```

data(co2temp)
names(co2temp)
table(co2temp$country)
lattice::xyplot(co2~year|country,data=co2temp,type="l",as.table=TRUE)

```

contrast

Function to compute the needed statistics for a given contrast

Description

The function computes the statistics for inference in a given contrast, subject to a given significance level. Those statistics are as follows: estimated contrast, standard error of the contrast, and the confidence interval of the contrast.

Usage

```

contrast(
  model = model,
  coef.cont = coef.cont,
  grp.m = grp.m,
  grp.n = grp.n,
  alpha = 0.05,
  full = TRUE
)

```

Arguments

<code>model</code>	object containing the fitted model
<code>coef.cont</code>	vector with the coefficients to establish the contrasts
<code>grp.m</code>	a vector having the sample mean per each group, or level of the factor under study.
<code>grp.n</code>	a vector having the sample size per each group, or level of the factor under study.
<code>alpha</code>	is the significance level for building the confidence intervals. Default value is 0.05, which is 95% confidence level.
<code>full</code>	FALSE if want short output, TRUE for longer (i.e. more details). Default is TRUE.

Details

The contrast is established based upon an already fitted statistical model that describe the relationship among variables. The significance level ('alpha') is defined by the user, although by default has been set to 0.05, that is to say, a 95% of statistical confidence.

Value

This function returns the above described statistics for a given contrast.

Author(s)

Christian Salas-Eljatib

References

- Salas-Eljatib C. 2025. datana: Datasets and Functions to Accompany Análisis de Datos con R. R package version 1.0.7, [doi:10.32614/CRAN.package.datana](https://doi.org/10.32614/CRAN.package.datana), <https://CRAN.R-project.org/package=datana>

Examples

```
data(fertiliza)
table(fertiliza$treat)
means.trt <- tapply(fertiliza$volume, fertiliza$treat, mean); means.trt
sds.trt <- tapply(fertiliza$volume, fertiliza$treat, sd); sds.trt
ns.trt <- tapply(fertiliza$volume, fertiliza$treat, length); ns.trt
m1 <- lm(volume ~ treat, data=fertiliza)
anova(m1)
## Coefficients to be used in the contrast
#c1: (tmoA1-A2) - (tmoA3-A4)
C1.coeff <- c(0, 1, 1, -1, -1)
contrast(model=m1, C1.coeff, grp.m=means.trt, grp.n=ns.trt, alpha=0.1, full=TRUE)
contrast(model=m1, C1.coeff, grp.m=means.trt, grp.n=ns.trt, alpha=0.1, full=FALSE)
contrast(m1, C1.coeff, grp.m=means.trt, grp.n=ns.trt, alpha=0.05, full=TRUE)
contrast(m1, C1.coeff, grp.m=means.trt, grp.n=ns.trt)
```

corkoak

Tree-level cork biomass data for Oak trees in Portugal

Description

Measurements of cork weight in *Quercus suber* (Oak) trees in Portugal.

Usage

corkoak

Format

tree A correlative number for each sample tree.

csc is tree circumference at 1.3 m outside bark, in cm.

cbe is tree circumference at 1.3 m under bark, in cm.

bt bark thickness, in cm.

hdeb is debarking height, in m.

hblc height to base of live crown, in m.

nb number of branches debarked

cr.diam crown diameter, in m.

w total green weight of the stripped cork, in kg

stratum Stratum

Source

Data supplied electronically to Prof. Timothy Gregoire (Yale University) by authors accompanied by a note which said "After the article was published we discovered a problem with 2 of the observations so Teresa and I decided it was best just to delete them."

References

- Fonseca TJ, Parresol BR. 2001. A new model for cork weight estimation in northern Portugal with methodology for construction of confidence intervals. *Forest Ecology and Management* 152(1):131–139.

Examples

```
data(corkoak)
head(corkoak)
```

corkoak2*Datos de biomasa de corcho en árboles de Encino en Portugal*

Description

Mediciones de peso de corcho en árboles muestra de *Quercus suber* en Portugal.

Usage

corkoak2

Format

arbol A correlative number for each sample tree.

perimetro.cc is tree circumference at 1.3 m outside bark, in cm.

perimetro.sc is tree circumference at 1.3 m under bark, in cm.

e.corteza bark thickness, in cm.

h.desc is debarking height, in m.

hcc height to base of live crown, in m.

num.ram number of branches debarked

diam.copa crown diameter, in m.

biomasa total green weight of the stripped cork, in kg

estrato Estrato

Source

Datos cedidos por Prof. Timothy Gregoire (Yale University) y los autores originales mencionaron "After the article was published we discovered a problem with 2 of the observations so Teresa and I decided it was best just to delete them."

References

- Fonseca TJ, Parresol BR. 2001. A new model for cork weight estimation in northern Portugal with methodology for construction of confidence intervals. *Forest Ecology and Management* 152(1):131–139.

Examples

```
data(corkoak2)
head(corkoak2)
```

deleteLeft	<i>Deletes the first n-characters of a string</i>
------------	---

Description

Function to delete the last n-characters of a string from the left-hand side.

Usage

```
deleteLeft(fac, n)
```

Arguments

fac	is an object of class string or factor
n	is the number of characters to be deleted of a the string given in 'fac'.

Details

It is specially set to arrange data vector having alphanumeric format.

Value

This function returns an object having n-less characters from the left-hand side.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
plot.id <- c("BNE1", "BNE2", "PLE1")
deleteLeft(plot.id, 1)
deleteLeft(plot.id, 2)
deleteLeft(plot.id, 3)
```

deleteRight	<i>Deletes the last n-characters of a string</i>
-------------	--

Description

Function to delete the last n-characters of a string from the right-hand side.

Usage

```
deleteRight(fac, n)
```

Arguments

fac	is an object of class string or factor
n	is the number of characters to be deleted of a the string given in 'fac'.

Details

It is specially set to arrange data vector having alphanumeric format.

Value

This function returns an object having n-less characters from the right-hand side.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
last.names.id <- c("Stage-1924", "Gregoire-1958", "Robinson-1967")
deleteRight(last.names.id, 5)
deleteRight(last.names.id, 4)
```

 descstat

Creates a descriptive statistics table for continuous variables.

Description

Function to create a descriptive statistics table for continuous variables from a dataframe.

Usage

```
descstat(data = data, decnum = 3, eng = TRUE, full = FALSE)
```

Arguments

data	a dataframe containing numeric variables as columns.
decnum	the number of decimals to be used in the output. The default is set to 3.
eng	logical; if "TRUE" (by default), the language of the statistics will be in English; if "FALSE" will be in Spanish. descriptive statistics. The default is to "FALSE".
full	logical; if "TRUE", the output includes some extra descriptive statistics. The default is to "FALSE".

Details

The resulting table offers the main central and dispersion statistics.

Value

This function wraps descriptive statistics into a summarize table having the following statistics: sample size, minimum, maximum, mean, median, SD, and coefficient of variation. If the "full" option is set to "TRUE", the following statistics will be added to the table: 25th and 75th percentiles, the interquartile range, skewness, and kurtosis.

Author(s)

Christian Salas-Eljatib and Tomas Cayul.

References

- Salas-Eljatib C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor. Santiago, Chile. <https://eljatib.com>

Examples

```
df <- datana::idahohd
head(df)
df.h<-df[,c("dbh", "height")]
## using the function
descstat(data=df.h)
descstat(data=df.h, decnum=1, eng=FALSE)
descstat(df.h, 2)
```

election	<i>Presidential election data of Florida (USA) in 2000.</i>
----------	---

Description

County-by-county vote for president in Florida in 2000 for Bush, Gore and Buchanan.

Usage

```
data(election)
```

Format

Contains three variables, as follows:

gore Vote for Gore.

bush Vote for Bush.

buchanan Vote for Pat Buchanan.

Source

The data were obtained from the *alr4* library.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. Hoboken NJ: Wiley

Examples

```
data(election)
head(election)
```

election2	<i>Elección presidencial en el estado de Florida (USA) en el 2000.</i>
-----------	--

Description

Conteo de votos a nivel de condado en el estado de Florida, año 2000.

Usage

```
data(election2)
```

Format

Contiene las siguientes tres columnas:

gore Votos para Gore. Número de votos para Al Gore.

bush Votos para Bush. Número de votos para George W. Bush.

buchanan Votos para Buchaman. Número de votos para Pat Buchanan.

Source

Los datos se obtuvieron desde el paquete *alr4* de R.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. Hoboken NJ: Wiley

Examples

```
data(election2)
head(election2)
```

eucaleaf

Leaf measurements for Eucalyptus nitens trees in Tasmania, Australia.

Description

The length, width, and area of Eucalyptus nitens leaves were measured.

Usage

```
data(eucaleaf)
```

Format

Contains leaf-level variables, as follows:

time Time factor, in two levels: early or Late.

tree Sample tree code identifier.

shoot Shoot description factor, in three levels.

l Length of the leaf, in mm.

w Width of the leaf, in mm.

la leaf area, in cm².

Source

Although the original source of the measurements is the Dissertation of Dr Candy (1999), the data file used here was courtesy of Prof. Timothy Gregoire at Yale University (New Haven, CT, USA). Furthermore, these data were used by Gregoire and Salas (2009).

References

- Candy SG. 1999. Predictive models for integrated pest management of the leaf beetle *Chrysophtharta bimaculata* in *Eucalyptus nitens* in Tasmania. Doctoral dissertation, University of Tasmania, Hobart, Australia.
- Gregoire TG, and Salas C. 2009. Ratio estimation with measurement error in the auxiliary variate. Biometrics 65(2):590-598 doi:10.1111/j.15410420.2008.01110.x

Examples

```
data(eucaleaf)
head(eucaleaf)
```

eucaleaf2	<i>Mediciones foliares para árboles de Eucalyptus nitens en Tasmania, Australia.</i>
-----------	--

Description

Mediciones de largo, ancho y area de hojas de Eucalyptus nitens.

Usage

```
data(eucaleaf2)
```

Format

Contiene variables a nivel de hoja, como sigue:

tiempo Factor a dos niveles: Temprano o Tardío.

arbol Identificador del árbol muestra.

meristema Factor de la descripción del meristema, en tres niveles.

largo Largo de la hoja, en mm.

ancho Ancho de la hoja, en mm.

area Área foliar, en cm².

Source

Aunque la fuente original de estas mediciones proviene de la tesis del Dr. Candy (1999), el archivo de datos fue cortesía del Prof. Timothy Gregoire de Yale University (New Haven, CT, USA). Además, estos datos fueron ocupados en el estudio de Gregoire y Salas (2009).

References

- Candy SG. 1999. Predictive models for integrated pest management of the leaf beetle *Chrysophtharta bimaculata* in *Eucalyptus nitens* in Tasmania. Doctoral dissertation, University of Tasmania, Hobart, Australia.
- Gregoire TG, and Salas C. 2009. Ratio estimation with measurement error in the auxiliary variate. *Biometrics* 65(2):590-598 doi:10.1111/j.15410420.2008.01110.x

Examples

```
data(eucaleaf2)
head(eucaleaf2)
```

eucaleafAll	<i>Leaf measurements (all, n=744) for Eucalyptus nitens trees in Tasmania, Australia.</i>
-------------	---

Description

The length, width, and area of *Eucalyptus nitens* leaves were measured for all the samples of Candy (1999).

Usage

```
data(eucaleafAll)
```

Format

Contains leaf-level variables, as follows:

time Time factor, in two levels: early or Late.

tree Sample tree code identifier.

shoot Shoot description factor, in three levels.

l Length of the leaf, in mm.

w Width of the leaf, in mm.

la leaf area, in cm².

Source

Although the original source of the measurements is the Dissertation of Dr Candy (1999), the data file used here was courtesy of Prof. Timothy Gregoire at Yale University (New Haven, CT, USA). Furthermore, these data were used by Gregoire and Salas (2009).

References

- Candy SG. 1999. Predictive models for integrated pest management of the leaf beetle *Chrysophtharta bimaculata* in *Eucalyptus nitens* in Tasmania. Doctoral dissertation, University of Tasmania, Hobart, Australia.

Examples

```
data(eucaleafA11)
head(eucaleafA11)
```

eucaleafA112	<i>Mediciones foliares (todas, n=744) para árboles de Eucalyptus nitens en Tasmania, Australia.</i>
--------------	---

Description

Mediciones de largo, ancho y área de hojas de Eucalyptus nitens para toda la muestra de Candy (1999).

Usage

```
data(eucaleafA112)
```

Format

Contiene variables a nivel de hoja, como sigue:

tiempo Factor a dos niveles: Temprano o Tardío

arbol Identificador del árbol muestra

meristema Factor de la descripción del meristema, en tres niveles.

largo Largo de la hoja, en mm

ancho Ancho de la hoja, en mm

area Área foliar, en cm²

Source

Aunque la fuente original de estas mediciones proviene de la tesis del Dr. Candy (1999), el archivo de datos fue cortesía del Prof. Timothy Gregoire de Yale University (New Haven, CT, USA).

References

- Candy SG. 1999. Predictive models for integrated pest management of the leaf beetle Chrysophtharta bimaculata in Eucalyptus nitens in Tasmania. Doctoral dissertation, University of Tasmania, Hobart, Australia.

Examples

```
data(eucaleafA112)
head(eucaleafA112)
```

extractLeft	<i>Extracts the last n-characters of a string</i>
-------------	---

Description

Function to extract the first n-characters of a string from the left-hand side.

Usage

```
extractLeft(fac, n)
```

Arguments

fac	is an object of class string or factor
n	is the number of characters to be deleted of a the string given in 'fac'.

Details

It is specially set to arrange data vector having alphanumeric format.

Value

This function returns an object having the first n-characters from the left-hand side.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
plot.id <- c("BNE1", "BNE2", "PLE1")
extractLeft(plot.id, 1)
extractLeft(plot.id, 2)
extractLeft(plot.id, 3)
```

extractRight	<i>Extracts the last n-characters of a string</i>
--------------	---

Description

Function to extract the last n-characters of a string from the right-hand side.

Usage

```
extractRight(fac, n)
```

Arguments

fac	is an object of class string or factor
n	is the number of characters to be deleted of a the string given in 'fac'.

Details

It is specially set to arrange data vector having alphanumeric format.

Value

This function returns an object having the last n characters from the right-hand side.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
last.names.id <- c("Stage-1924", "Gregoire-1958", "Robinson-1967")
extractRight(last.names.id, 4)
extractRight(last.names.id, 2)
```

fertiliza	<i>Fertilization experiment data.</i>
-----------	---------------------------------------

Description

Data contains volume data at plot-level for a fertilization experiment.

Usage

```
data(fertiliza)
```

Format

Contains two variables, as follows:

treat Treatment level.

volume Plot-level volume, in m³.

Source

The data were provided by Dr Christian Salas-Eljatib (Universidad de Chile, Santiago, Chile).

References

not yet

Examples

```
data(fertiliza)
head(fertiliza)
class(fertiliza$treat)
unique(fertiliza$treat)
means.g <- tapply(fertiliza$volume,fertiliza$treat,mean);means.g
sds.g <- tapply(fertiliza$volume,fertiliza$treat,sd);sds.g
ns.g <- tapply(fertiliza$volume,fertiliza$treat,length);ns.g
```

fertiliza2	<i>Experimento de fertilización</i>
------------	-------------------------------------

Description

Datos a nivel de parcela de un experimento de fertilización con tratamientos y replicas.

Usage

```
data(fertiliza2)
```

Format

Contiene tres columnas como sigue:

tmo Tratamiento.Factor medido en diferentes niveles.

vol Volumen de madera en la parcela experimental, en m³.

Source

Datos cedidos por el Prof. Christian Salas.

References

not yet

Examples

```
data(fertiliza2)
head(fertiliza2)
class(fertiliza2$tmo)
unique(fertiliza2$tmo)
media.g <- tapply(fertiliza2$vol,fertiliza2$tmo,mean);media.g
desvst.g <- tapply(fertiliza2$vol,fertiliza2$tmo,sd);desvst.g
n.g <- tapply(fertiliza2$vol,fertiliza2$tmo,length);n.g
```

ficdiamgr

Diameter growth of trees

Description

The 'ficdiamgr' is a fictitious dataframe built to show the structure of longitudinal data. The dataframe has records of tree diameter growth of five sample trees, spanning three species.

Usage

```
data(ficdiamgr)
```

Format

A time series data containing the following columns:

tree.id an ordered factor indicating the tree on which the measurement is made. The ordering is according to increasing maximum diameter.

time a numeric vector giving the numbers of days since establishment.

dbh a numeric vector of diameter at breast height, in cm.

site a factor variable, representing site conditions with two levels.

spp a factor variable, representing tree species with three levels.

Source

This dataframe was built from the 'Orange' data of the *datasets* package, by Christian Salas-Eljatib.

Examples

```
data(ficdiamgr)

coplot(dbh ~ time | tree, data = ficdiamgr, show.given = FALSE)
```

ficdiamgr2	<i>Crecimiento diametral de árboles</i>
------------	---

Description

Los datos 'ficdiamgr2' son ficticios, y fue construida para mostrar la estructura de datos longitudinales. Los datos tienen registro de crecimiento en cinco árboles muestra, representando a tres especies.

Usage

```
data(ficdiamgr2)
```

Format

Una serie de tiempo conteniendo las siguientes columnas:

- arbol** indica el identificador del árbol.
- tiempo** número de días desde el inicio de las mediciones.
- dap** diámetro a la altura del pecho, en cm.
- sitio** un factor, representando condiciones de sitio, en dos niveles.
- espe** un factor, representando especie del árbol, en tres niveles.

Source

Estos datos fueron modificados desde la dataframe 'Orange' de la librería 'datasets', por Christian Salas-Eljatib.

Examples

```
data(ficdiamgr2)

coplot(dap ~ tiempo | arbol, data = ficdiamgr2, show.given = FALSE)
```

findColumn.byname	<i>Finds the position of a specific variable.</i>
-------------------	---

Description

Sometimes in data manipulation we face the task of locating the position of a specific variable within a dataframe. The function finds the position in which a column name is within an object.

Usage

```
findColumn.byname(data = data, col.name = col.name)
```

Arguments

data	is a dataframe
col.name	is a string specifying the name of the variable

Details

Although the function finds the position of a specific variable, can also be used for more than one variable.

Value

This function returns the number of a specific column-name.

Note

It can be used for a vector of specified column-names as well.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
df <- data.frame(varX=1:5, varY=letters[1:5], varZ=rep("a",5),
varK=rep("b",5))
df
#using the function
findColumn.byname(df, c("varY","varZ"))
findColumn.byname(df, "varK")
#Creating an example vector
vector <- letters
```

```
vector
findColumn.byname(vector, c("h", "z"))
```

fishgrowth	<i>Fish growth variables.</i>
------------	-------------------------------

Description

Variables of small mouth bass (i.e, a fish) collected in West Bearskin Lake, Minnesota, in 1991.

Usage

```
data(fishgrowth)
```

Format

Contains three variables, as follows:

years Year at capture.

length Length at capture (mm).

scale radius of a key scale (mm).

Source

The data were obtained from the *alr4* library of R, specifically from the dataframe *wblake* that includes only fish of ages 8 or younger.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. Hoboken NJ: Wiley

Examples

```
data(fishgrowth)
head(fishgrowth)
plot(length~age, data=fishgrowth)
```

fishgrowth2	<i>Crecimiento de peces</i>
-------------	-----------------------------

Description

Variables de crecimiento de peces en el lago West Bearskin del estado de Minnesota, en 1991.

Usage

```
data(fishgrowth2)
```

Format

Contiene tres variables, como sigue:

edad Year at capture.

largo Length at capture, en mm.

escala radius of a key scale, en mm.

Source

Datos obtenidos desde el paquete *alr4* de R, de la dataframe *wblake* que incluye peces de hasta 8 años.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. Hoboken NJ: Wiley

Examples

```
data(fishgrowth2)
head(fishgrowth2)
plot(largo~edad,data=fishgrowth2)
```

forestfire	<i>Forest fire occurrence in central Chile</i>
------------	--

Description

Data of forest fire occurrence in central Chile having 7210 observations, with 890 cases of fire occurrence and 6320 cases of non-occurrence. The binary variable (Y) is the occurrence of forest fire, where $Y = 1$ to denotes occurrence and $Y = 0$, otherwise.

Usage

```
data(forestfire)
```

Format

The data frame contains four variables as follows:

fire Occurrence of forest fire (1 yes, 0 no)
xcoord Geographic coordinate x.utm
ycoord Geographic coordinate y.utm
aspect Exposure (degrees from north)
eleva Elevation (m)
slope Slope (degrees)
distr Distance to dirt roads
distcity Distance to cities
distriver Distance to paved roads
covera Land use classifications according to a polygon
coverb Land use classifications according to a polygon
tempe Minimum temperature of the coldest month
ppan Annual precipitation
ndii Normalized difference infrared index
nvgi Normalized difference vegetation index
tempe2 Minimum temperature of the warmest month
ppan2 Precipitation of the driest month
frec.fire Frequency of fires
perc.fire Percentage of fire frequency
fireClass Class for frequency fire
asp.class Class of variable exposure
eleva.class Class of numerical variable elevation
slope.class Class of numerical variable slope
ndii.class Normalized difference infrared index class
nvgi.class Normalized difference vegetation index class

Source

Data were provided by Dr Adison Altamirano at the Universidad de La Frontera (Temuco, Chile).

References

- Salas-Eljatib C, Fuentes-Ramírez A, Gregoire TG, Altamirano A, Yaitul V. 2018. A study on the effects of unbalanced data when fitting logistic regression models in ecology. *Ecological Indicators* 85:502-508. doi:10.1016/j.ecolind.2017.10.030
- Altamirano A, Salas C, Yaitul V, Smith-Ramirez C, Avila A. 2013. Influencia de la heterogeneidad del paisaje en la ocurrencia de incendios forestales en Chile Central. *Revista de Geografia del Norte Grande*, 55:157-170.

Examples

```
data(forestfire)
head(forestfire)
```

forestfire2

Ocurrencia de incendios forestales

Description

Datos de ocurrencia de incendios forestales en la zona central de Chile. Se tienen 7210 observaciones, de las cuales 890 tienen ocurrencia de incendios y 6320 casos de no ocurrencia. La variable binaria (Y) es la ocurrencia de un incendio forestal, donde $Y = 1$ denota ocurrencia y $Y = 0$, lo contrario.

Usage

```
data(forestfire2)
```

Format

Variables se describen a continuacion:

fire Presencia de incendio forestal (1 si, 0 no)
xcoord Coordenada geografica x.utm
ycoord Coordenada geografica y.utm
aspect Exposicion (grados desde el norte)
eleva Elevacion (m)
slope Pendiente (grados)
distr Distancia a caminos de tierra
distcity Distancia a ciudades
distriver Distancia a caminos pavimentados
covera Clasificaciones de uso del suelo segun un poligono
coverb Clasificaciones de uso del suelo segun un poligono
tempe Temperatura m?nima del mes m?s frio
ppan Precipitacion anual
ndii Indice infrarrojo de diferencia normalizado
nvd Indice de vegetacion de diferencia normalizado
tempe2 Temperatura m?nima del mes mas calido
ppan2 Precipitacion del mes mas seco
frec.fire Frecuencia de incendios
perc.fire Porcentajede la frecuencia de incendios

fireClass Clase para variable frecuencia de incendio
asp.class Clase de variable exposicion
eleva.class Clase de variable numerica elevacion
slope.class Clase de variable numerica pendiente
ndii.class Clase de indice infrarrojo de diferencia normalizado
nvdi.class Clase de indice de vegetacion de diferencia normalizado

Source

Datos fueron cedidos por el Dr. Adison Altamirano, Universidad de La Frontera, Temuco, Chile.

References

- Salas-Eljatib C, Fuentes-Ramírez A, Gregoire TG, Altamirano A, Yaitul V. 2018. A study on the effects of unbalanced data when fitting logistic regression models in ecology. *Ecological Indicators* 85:502-508. doi:10.1016/j.ecolind.2017.10.030
- Altamirano A, Salas C, Yaitul V, Smith-Ramirez C, Avila A. 2013. Influencia de la heterogeneidad del paisaje en la ocurrencia de incendios forestales en Chile Central. *Revista de Geografia del Norte Grande*, 55:157-170.

Examples

```
data(forestfire2)
head(forestfire2)
```

gdpcap	<i>Datos GDP-per capita</i>
--------	-----------------------------

Description

Datos del producto interno bruto per capita, por pais.

Usage

```
data(gdpcap)
```

Format

Este set de datos contiene las siguientes columnas:

- pais** Nombre del país.
- pais.cod** Codificación del país.
- gdp.pc** GDP per capita, en US dollars.
- y** GDP per capita, en miles de US dollars.

Source

Los datos fueron obtenidos desde la web <https://data.worldbank.org/indicator/NY.GDP.PCAP.CD>

Examples

```
data(gdpcap)
head(gdpcap)
unique(gdpcap$pais)
hist(gdpcap$y, breaks=20, xlab='PIB per capita (miles de US$)', col='orange', las=1)
```

gmean

Function to compute the geometric mean of a numeric vector

Description

Computes the geometric mean of a numeric vector. It is the n-th root of the product of n numbers, as follows.

$$y_g = \left(\prod_{i=1}^n y_i \right)^{1/n}$$

for $y_i > 0$. The geometric mean can be used a central position statistics of a random variable.

Usage

```
gmean(v)
```

Arguments

v is a numeric vector

Details

Notice that can only be computed for positive values. For negative values, there are alternatives, but not covered here.

Value

This function returns the geometric mean, a numeric scalar.

Author(s)

Christian Salas-Eljatib.

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
y.var <- runif(10, min=10, max=45)
gmean(y.var)
```

hgrdfir	<i>Tree height growth of Douglas-fir sample trees in the Northwest of the United States</i>
---------	---

Description

Data contains 148 observations on the height growth of dominant trees of *Pseudotsuga mensiezi* in the Northwest of the United States.

Usage

```
data(hgrdfir)
```

Format

The data frame contains seven variables as follows:

natfor.id Code identifier.

plot.code Plot number identification

tree.code Tree number identification.

dbh Diameter at breast height at sampling, in in.

toth Total height at sampling, in ft.

age Age of tree, yr.

height Height at a given age, in ft.

Source

The data were provided by Dr Christian Salas.

References

- Monserud RA. 1984. Height growth and site index curves for Inland Douglas-fir based on stem analysis data and forest habitat type. *Forest Science* 30(4):943-965.
- Salas C, Stage AR, and Robinson AP. 2008. Modeling effects of overstory density and competing vegetation on tree height growth. *Forest Science* 54(1):107-122. doi:10.1093/forests/54.1.107

Examples

```
data(hgrdfir)
head(hgrdfir)
unique(hgrdfir$tree.code)
table(hgrdfir$plot.code, hgrdfir$tree.code)
tapply(hgrdfir$dbh, hgrdfir$tree.code, mean)
tapply(hgrdfir$dbh, hgrdfir$tree.code, mean) #dbh of each sample tree
tapply(hgrdfir$toth, hgrdfir$tree.code, mean) #toth of each sample tree
```

hgrdfir2	<i>Crecimiento en altura de una muestra de árboles en los Estados Unidos</i>
----------	--

Description

Data contiene 148 observaciones sobre el crecimiento en altura de árboles dominantes de *Pseudotsuga mensiezi* en el Nor-Oeste de los Estados Unidos

Usage

```
data(hgrdfir2)
```

Format

La data frame contiene siete variables:

bosque.id Código identificador del bosque.

parcela Código identificador de la parcela.

arbol Número de identificación árbol.

dap Diámetro a la altura del pecho, en pulgadas.

atot Altura total, en pies

edad Edad, en os

altura Altura para cada edad del árbol, en pies

Source

La data fue cedida por el Dr Christian Salas-Eljatib.

References

Monserud RA. 1984. Height growth and site index curves for Inland Douglas-fir based on stem analysis data and forest habitat type. *Forest Science* 30(4):943-965.

Salas C, Stage AR, and Robinson AP. 2008. Modeling effects of overstory density and competing vegetation on tree height growth. *Forest Science* 54(1):107-122. doi:[10.1093/forestscience/54.1.107](https://doi.org/10.1093/forestscience/54.1.107)

Examples

```
data(hgrdfir2)
head(hgrdfir2)
unique(hgrdfir2$arbol.id)
table(hgrdfir2$parcela,hgrdfir2$arbol.id)
tapply(hgrdfir2$dap, hgrdfir2$arbol.id, mean) #dap de cada arbol muestra
tapply(hgrdfir2$atot, hgrdfir2$arbol.id, mean) #atot de cada arbol muestra
```

hmean

*Function to compute the harmonic mean of a numeric vector***Description**

Computes the harmonic mean of a numeric vector. It is the inverse of the mean of the reciprocals of n numbers, as follows.

$$y_h = \frac{n}{\left(\sum_{i=1}^n \frac{1}{y_i}\right)}$$

for $y_i \neq 0$. The harmonic mean can be used a central position statistics of a random variable.

Usage

```
hmean(v)
```

Arguments

`v` is a numeric vector

Details

Notice that can only be computed for values different from zero.

Value

This function returns the harmonic mean, a numeric scalar.

Author(s)

Christian Salas-Eljatib.

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
y.var <- runif(10, min=10, max=45)
hmean(y.var)
```

idahohd*Tree height-diameter data from Idaho (USA)*

Description

These data are forest inventory measures from the Upper Flat Creek stand of the University of Idaho Experimental Forest, dated 1991.

Usage

```
data(idahohd)
```

Format

Contains five variables, as follows:

plot Plot number.

tree Tree within plot.

species A factor with levels DF = Douglas-fir, GF = Grand fir, SF = Subalpine fir, WL = Western larch, WC = Western red cedar, WP = White pine.

dbh Diameter 137 cm perpendicular to the bole, cm.

height Height of the tree, in m.

Source

The data were assembled from the 'ufc' dataframe from the *alr4* library.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. New York: Wiley.

Examples

```
data(idahohd)
head(idahohd)
plot(height~dbh, data=idahohd)
```

`idahohd2`*Altura-diámetro de árboles en el estado de Idaho (USA)*

Description

Estos datos provienen de un muestreo en el bosque experimental de la University of Idaho, en Upper Flat Creek, Idaho, USA. Medido en 1991.

Usage

```
data(idahohd2)
```

Format

Contiene cinco variables detalladas a continuación:

parce Número de la parcela de muestreo.

arbol Número del árbol dentro de la parcela.

spp Especie del árbol, una variable factor con niveles DF = Douglas-fir, GF = Grand fir, SF = Subalpine fir, WL = Western larch, WC = Western red cedar, WP = White pine.

dap Diámetro del fuste a los 1.3 m sobre el suelo, en cm.

atot Altura del árbol, en m.

Source

Los datos fueron obtenidos desde la dataframe 'ufc' de la librería *alr4*.

References

Weisberg S. 2014. Applied Linear Regression. 4th edition. New York: Wiley.

Examples

```
data(idahohd2)
head(idahohd2)
plot(atot~dap, data=idahohd2)
```

kurto	<i>Computes the sample kurtosis of a distribution</i>
-------	---

Description

The kurtosis is about the tailedness, or the degree of heaviness of the tails, in the frequency distribution. The function computes an estimator of the kurtosis.

Usage

```
kurto(x, na.rm = TRUE)
```

Arguments

x	a numeric vector of a random variable.
na.rm	logical operator to remove NA values. The default is set to TRUE.

Details

The kurtosis of a random variable is the fourth moment of the standardized variable. There are several ways of parameterizing a kurtosis estimator, such as depending on the fourth moment and the standard deviation of the random variable.

Value

An estimator of the kurtosis.

Author(s)

Christian Salas-Eljatib

Examples

```
y.var<-rnorm(100);x.var<-rbeta(100,.2,2)
kurto(y.var)
kurto(x.var)
```

landcover

Land-cover, environmental and sociodemographic data for the 34 municipalities composing the Greater Santiago area, Santiago, Chile.

Description

dataset contains 476 observations, 34 categorical and 442 numerical. Land-cover data was generated through remote sensing classification techniques using Sentinel-2 satellite images from year 2016. Temperatures were obtained from TIRS band 10 of Landsat 8 satellites images. Particulate matter concentrations were estimated using spatial modelling techniques from 10 pollution stations distributed in the city. Altitude was generated from a Digital Elevation Model. Population and poverty were gathered from Casen 2017 survey.

Usage

```
data(landcover)
```

Format

The data frame contains four variables as follows:

county Name of Municipality

built.p Percentage of surface covered by built-up area

vegeta.p Percentage of surface covered by vegetation

naked.p Percentage of surface covered by bare soil

grass.p Percentage of surface covered by deciduous vegetation

p.Deciduo Percentage of surface covered by evergreen vegetation

p.Siempreverde Percentage of surface covered by evergreen vegetation

temp.winter Land surface temperature in celsius degrees at 2pm on a winter 0% cloud day

temp.summer Land surface temperature in celsius degrees at 2pm on a summer 0% cloud day

pm10.winter Average particulate matter 10 micron during winter months

pm10.summer Average particulate matter 10 micron during summer months

poor.p Percentage of people under poverty line year 2017.

eleva Average altitude of municipal area.

pop Total population of municipality

Source

Data were provided by Dr Ignacio Fernandez at Universidad Adolfo Ibañez (Santiago, Chile).

References

Not yet

Examples

```
data(landcover)
head(landcover)
```

landcover2	<i>Cobertura territorial, ambiental y sociodemografica de los 34 municipios que componen el area del Gran Santiago, Santiago, Chile..</i>
------------	---

Description

El conjunto de datos contiene 476 observaciones, 34 categoricas y 442 numericas. Los datos de cobertura terrestre se generaron mediante tecnicas de clasificacion de teledeteccion utilizando imagenes de satelite Sentinel-2 del año 2016. Las temperaturas se obtuvieron de la banda TIRS 10 de las imagenes de los satelites Landsat 8. Las concentraciones de material particulado se estimaron mediante tecnicas de modelado espacial de 10 estaciones de contaminacion distribuidas en la ciudad. La altitud se genero a partir de un modelo de elevacion digital. La poblacion y la pobreza se obtuvieron de la encuesta Casen 2017.

Usage

```
data(landcover2)
```

Format

Variables se describen a continuacion:

comuna Name of Municipality

const.p Porcentaje de superficie cubierta por area construida

vegeta.p Porcentaje de superficie cubierta por vegetacion

desnu.p Porcentaje de superficie cubierta por suelo desnudo

pasto.p Porcentaje de superficie cubierta por cespel

deci.p Porcentaje de superficie cubierta por vegetacion de hoja caduca

sverde.p Porcentaje de superficie cubierta por vegetacion siempre verde

temp.inv Temperatura de la superficie terrestre en grados celsius a las 2 p.m.en un dia de invierno con 0% de nubes

temp.ver Temperatura de la superficie de la tierra en grados celsius a las 2 p.m.en un dia de verano con 0% de nubes

pm10.inv Material particulado promedio de 10 micrones durante los meses de invierno

pm10.ver Material particulado promedio de 10 micrones durante los meses de verano

pobreza.p Porcentaje de personas por debajo de la linea de pobreza año 2017

altitud Altitud media del termino municipal

pob Poblacion total del municipio

Source

Los datos fueron cedidos por el Dr Ignacio Fernandez de la Universidad Adolfo Ibañez (Santiago, Chile).

References

Not yet

Examples

```
data(landcover2)
head(landcover2)
```

largetrees

Large trees in forests near Tolga, in Eastern Norway.

Description

The study area is situated in the municipality of Tolga, located in Hedmark County, Eastern Norway. Field plots 32 m × 32 m in size were established in forests. A total of 1109 plots were sampled. In each plot, Scots pines (*Pinus sylvestris* L.). trees with a stem diameter larger than 35 cm were measured and counted.

Usage

```
data(largetrees)
```

Format

Contains two variables, as follows:

plot Plot code.
y Number of large-diameter trees in a given sample plot.

Source

Although Christian Salas was part of the study, he just reproduced the needed data to mimic the distribution of the random variable of interest, as shown in the study of Korkhonen et al (2016).

References

- Korkhonen L, Salas C, Ostgard T, Lien V, Gobakken T, Naesset E. 2016. Predicting the occurrence of large-diameter trees using airborne laser scanning. Canadian Journal of Forest Research 46:461–469. doi:10.1139/cjfr20150384

Examples

```
data(largetrees)
head(largetrees)
hist(largetrees$y)
```

largetrees2*Árboles grandes en bosques cercanos a Tolga, en el Este de Noruega.*

Description

El área de estudio esta ubicada en la municipalidad de Tolga, en la comuna de Hedmark, al Este de Noruega. 1109 parcelas de muestreo de 32 m × 32 m se establecieron en los bosques. En cada parcela, los árboles de pino escoses (*Pinus sylvestris* L.). que tuvieran un diámetro mayor a 35 cm fueron medidos y contados.

Usage

```
data(largetrees2)
```

Format

Los datos poseen las siguientes dos columnas:

parc Identificador de la parcela de muestreo.

y Número de árboles de gran diámetro encontrados en una parcela de muestreo.

Source

Aunque el Prof. Christian Salas fue parte del estudio, acá se han reproducido los datos necesarios que imitan la distribución de la variable aleatoria de interés, tal como se muestra en el estudio de Korkhonen et al (2016).

References

- Korkhonen L, Salas C, Ostgard T, Lien V, Gobakken T, Naesset E. 2016. Predicting the occurrence of large-diameter trees using airborne laser scanning. Canadian Journal of Forest Research 46:461–469. doi:10.1139/cjfr20150384

Examples

```
data(largetrees2)
head(largetrees2)
hist(largetrees2$y)
```

lifexpect

*Esperanza de vida de paises***Description**

El repositorio del Observatorio Mundial de la Salud (GHO) de la Organización Mundial de la Salud (WHO) mantiene un registro del estado de salud como también otros factores relacionados, para todos los países. Las bases de datos son publicadas con el objetivo de analizarlos. La base de datos de esperanza de vida ha sido compilada en conjunto con datos económicos de las Naciones Unidas.

Usage

```
data(lifexpect)
```

Format

Este set de datos contiene 22 columnas:

country País de origen

year Año

status Categoría del país Desarrollado/En desarrollo

life.expectancy Esperanza de vida en años

adult.mortality Mortalidad en adultos expresado como la probabilidad de morir entre 15 y 60 años de edad por cada 1000 habitantes

infant.deaths Mortalidad en infantes cada 1000 habitantes

alcohol Consumo de alcohol percapita en mayores de 15 años

percentage.expenditure Porcentaje de vacunación

hepatitis.b Porcentaje de vacunación contra hepatitis b

measles Casos de sarampión cada 1000 habitantes

bmi Índice de masa corporal (BMI) promedio

under.five.deaths Muertes de menores de 5 años cada 1000 habitantes

polio Porcentaje de vacunación contra polio

total.expenditure Inversión en salud como porcentaje del GDP per cápita

diphtheria Porcentaje de vacunación contra diphtheria

hiv.aids Porcentaje casos de VIH, ETS

gdp GDP per cápita en USD

population Población total

thinness10.19 Desnutrición entre 10 y 19 años de edad

thinness5.9 Desnutrición entre 5 y 9 años de edad

icr Índice de desarrollo humano en términos de composición de ingresos

schooling Promedio de años de educación

Source

Los datos fueron obtenidos desde la web <https://rpubs.com/Alvian2022/LifeExpectancy>.
Note que solo los datos del año 2014 son utilizados acá.

Examples

```
data(lifexpect)
head(lifexpect)
table(lifexpect$status)
tapply(lifexpect$life.expectancy, lifexpect$status, mean)
```

llancahue	<i>Tree locations for a sample plot in the Llancahue experimental forest</i>
-----------	--

Description

The Cartesian position, species, and diameter of trees within a plot were measured. The sample plot is rectangular of 130 m by 70 m. Further details can be #' reviewed in the reference.

Usage

```
data(llancahue)
```

Format

Contains tree-level variables, as follows:

tree.code Tree identifier

spp species abbreviation as follows: AP=Aextocicon punctatum, EC=Eucryphia cordifolia, GA=Gevuina avellana, LP=Laureliopsis philippiana, LS=Laurelia sempervirens, ND=Nothofagus dombeyi, Ot=Other, PS=Podocarpus saligna

dbh diameter at breast height, in cm.

x.coord Cartesian position in the X-axis, in m.

y.coord Cartesian position in the Y-axis, in m.

Source

The data are provided courtesy of Prof. Daniel Soto at Universidad de Aysen (Coyhaique, Chile).

References

- Soto DP, Salas C, Donoso PJ, Uteau D. 2010. Heterogeneidad estructural y espacial de un bosque mixto dominado por Nothofagus dombeyi después de un disturbio parcial. Revista Chilena de Historia Natural 83(3): 335-347.

Examples

```
data(llancahue)
head(llancahue)
descstat(llancahue$dbh)
boxplot(dbh~spp, data=llancahue)
```

llancahue2

Ubicación cartesiana de árboles en el bosque de Llancahue

Description

Corresponde a la posición cartesiana, especie, y diámetro de árboles en una parcela de muestreo en el bosque de Llancahue, cerca de Valdivia, Chile. La parcela es rectangular con dimensiones de 130 m por 70 m. Mayores antecedentes aparecen en las referencias.

Usage

```
data(llancahue2)
```

Format

Contains tree-level variables, as follows:

arb.id Identificador del árbol.

spp Codificación de la especie como sigue: AP=Aextocicon punctatum, EC=Eucryphia cordifolia, GA=Gevuina avellana, LP=Laureliopsis philippiana, LS=Laurelia sempervirens, ND=Nothofagus dombeyi, Ot=Other, PS=Podocarpus saligna.

dap Diámetro a la altura del pecho, en cm.

coord.x Posición cartesiana en el eje-X, en m.

coord.y Posición cartesiana en el eje-Y, en m.

Source

Los datos fueron cedidos por el Prof. Daniel Soto de Universidad de Aysen (Coyhaique, Chile).

References

- Soto DP, Salas C, Donoso PJ, Uteau D. 2010. Heterogeneidad estructural y espacial de un bosque mixto dominado por Nothofagus dombeyi después de un disturbio parcial. Revista Chilena de Historia Natural 83(3): 335-347.

Examples

```
data(llancahue2)
head(llancahue2)
descstat(llancahue2$dap)
boxplot(dap~spp, data=llancahue2)
```

lrt	<i>Performs a likelihood ratio test between two models being fitted by maximum likelihood.</i>
-----	--

Description

Function to perform a likelihood ratio test (LRT) between a reduced model (modA) versus a more complex model (modB), provided both models were fitted by maximum likelihood. The function requires to be filled with the needed values used to perform a LRT.

Usage

```
lrt(
  llma = llma,
  llmb = llmb,
  qa = qa,
  qb = qb,
  nfit = nfit,
  modA = "modA",
  modB = "modB",
  alpha = 0.05
)
```

Arguments

llma	maximized log-likelihood of the reduced model (or modA).
llmb	maximized log-likelihood of the more-complex model (or modB).
qa	the number of parameters of the reduced model.
qb	the number of parameters of the more-complex model.
nfit	the sample size used for fitted both models.
modA	is a character with a name to be assigned to object modA.
modB	is a character with a name to be assigned to object modB.
alpha	is the level of significance to used for computing as a reference only, the tabulated value of the respective Chi-Squared statistic. By the default is set to 0.05.

Details

The resulting output offers statistical inference estimates of the LRT, as well as other maximum likelihood-based statistics. Notice that the function only works if the number of parameters for modA is lower than the ones of modB.

Value

This function wraps two outputs: (i) a table that computes the AIC, BIC and AICc goodness-of-fit statistics for both models, and (ii) the result of the likelihood ratio test, such as the value of the statistic being computed, its respective p-value, and the tabulated value of the statistics using the a defined alpha significance of level.

Author(s)

Christian Salas-Eljatib.

References

Salas-Eljatib, C. 2025. Estadística Aplicada e Inferencial. Borrador de libro, Universidad de Chile, Santiago, Chile. <https://eljatib.com/rlibro>

Examples

```
#Maximized values for two probability mass functions
max.ll.pois<- -39.86337; max.ll.bneg<--33.823003
c(max.ll.pois,max.ll.bneg)
sample.size<-26
#Number of parameters
num.para.pois<- 1; num.para.bneg<- 3
c(num.para.pois, num.para.bneg)
#Names to be used for each model
modA="Poisson"; modB="hiper"
outall<-lrt(llma=max.ll.pois,llmb=max.ll.bneg,qa=num.para.pois,
qb=num.para.bneg,nfit = sample.size,modA = "Poisson",
modB = "Hipergeometrico")
#Output1: A comparative table
tab.out<-outall$tab.models
tab.out
#Output2: the results of the LRT
out<-outall$lrt.out
out$r.tab
out$Ldif
```

lrt.glm	<i>Computes a likelihood ratio test between a reduced model and a full model. Both models must be already fitted using and R function.</i>
---------	--

Description

Computes a likelihood ratio test between a reduced model (modr) and a full model (modf). Both models must be previously fitted by maximum likelihood using an R function such as nlme() and such, that are part of the generalized lineal models.

Usage

```
lrt.glm(modr, modf)
```

Arguments

- modr is the object containing a previously fitted reduced model, using a glm-type of function, having less parameters than modf.
- modf is the object containing a previously fitted full model, using a glm-type of function, having more parameters than modr.

Details

Double-check the order of the reduced and full model, before of using the model

Value

This function returns an object having the following elements: "loglik.Modr" maximized log-likelihood of modr; "loglik.Modf" maximized log-likelihood of modf; "dif.loglik" difference in log-likelihood between both models, and "dif.df" difference in degrees of freedom of both models, and "p-value" is the p-value for the LRT.

Author(s)

Christian Salas-Eljatib.

References

Pinheiro JC, and Bates DM. 2000. Mixed-effects models in S and Splus. Springer-Verlag, New York, NY. 528 p.

Examples

```
#not yet implemented
```

moda

Computes the mode

Description

Computes the mode of a random variable.

Usage

```
moda(y = y)
```

Arguments

y is a numeric vector.

Details

The mode is an statistics representing the most "used" value of the random variable as a way of central position.

Value

The function returns the mode, a numeric scalar.

Author(s)

Christian Salas-Eljatib.

Examples

```
set.seed(1234)
variable <- rnorm(10, mean=45, sd=6)
#using the function
moda(y=variable)
moda(variable)
```

papersdocstu

Productividad científica de estudiantes de postgrado

Description

Corresponde a un estudio realizado en la Universidad de Indiana, sobre el número de papers publicados por estudiantes egresados de programas de doctorado en bioquímica luego de 3 años.

Usage

```
data(papersdocstu)
```

Format

Este set de datos contiene las siguientes columnas:

papers Es el número de artículos científicos publicados luego de 3 años de egresado.

genero Hombre/mujer.

est.civil Estado civil del egresado.

nin.men5 Número de hijos menores a 6 años que dependen del egresado.

prog.prest Puntaje asignado al prestigio del programa de postgrado.

papers.guia Número de papers publicados por el profesor(a) guía del egresado, en el mismo periodo de tiempo.

Source

Los datos fueron obtenidos desde el paquete 'AER'.

References

Long, J.S. (1997). The Origin of Sex Differences in Science.

Examples

```
data(papersdocstu)
df<-papersdocstu
head(df)
barplot(table(df$papers),xlab="Numero de papers publicados",
        ylab="Frecuencia (num. de estudiantes)")
table(df$genero)
table(df$est.civil,df$genero)
tapply(df$papers,df$est.civil,summary)
```

presenceIce	<i>Presence or absence of sea ice from logbook records of annual cruises</i>
-------------	--

Description

Data containing 52717 observations about presence of sea ice from logbook records of annual cruises to the B-C-B in an unbroken record between years 1850 to 1910.

Usage

```
data(presenceIce)
```

Format

The dataframe contains the following columns:

ship.id The code number for ships.

move.type Type of movement of ships. 0 indicates a sail-powered vessel and 1 indicates an auxiliary-powered vessel.

year Year of registry.

month Month of registry.

day Day of registry.

lat.dec Decimal latitude.

long.dec Decimal longitude.

e.w East or west of the Prime Meridian.

ice.cov Sea Ice Observed. 0 no see (Not registered) and 1 presence sea ice (Registered).

Source

The data were provided from Sea Ice Group at the Geophysical Institute.

References

Mahoney A, Bockstoce J, Botkin D, Eicken H, Nisbet R. 2011. Sea-Ice Distribution in the Bering and Chukchi Seas: Information from Historical Whaleships' Logbooks and Journals ARCTIC. 64(4): 465-477.

Examples

```
data(presenceIce)
head(presenceIce)
```

president

Eleccion presidencial del 2021 en Chile.

Description

Datos de mesa de la eleccion presidencial del 2012 en Chile. La eleccion se llevo a cabo el 19 de Diciembre del 2021.

Usage

```
data(president)
```

Format

Los datos contienen las siguientes columnas:

region.no Número de la region adminisitrativa de Chile.

region Nombre de la region administrativa de Chile

provincia Provincia.

circu.senatorial Circunscripcion senatorial.

distrito Distrit.

comuna County.

circu.elec Circunscripcion electoral.

local Local de votacion. Generalmente es un colegio.

no.mesa Número de mesa.

tipo.mesa Tipo de mesa de votacion.

mesas.fusionadas Mesa de votacion fucionada.

electores Electores.

nro.en.voto .

candidato Candidato, ya sea Gabriel Boric o Jose A. Kast

votos.tricel Número total de votos segun el TRICEL (Tribunal calificador de elecciones).

Source

Los datos fueron obtenidos desde el sitio web del Servicio Electoral del Gobierno de Chilean (SERVEL) en <https://www.servel.cl>. El archivo de datos descargado el 24 de Octubre del 2022 tenia el nombre Resultados mesa presidencial TRICEL 2v 2021-1.xlsx.

Examples

```
data(president)
head(president)
```

primarias*Elección primaria para la presidencia de Chile*

Description

Datos a nivel de mesa de la votación para elecciones primarias para Presidente de Chile en 2021.

Usage

```
data(primarias)
```

Format

Este set de datos contiene las siguientes columnas:

region.no Región administrativa de Chile.

region Nombre de la región.

provincia Provincia.

distrito Distrito.

comuna Comuna.

circu.elec Circunscripción electoral.

local Local de votación.

tipo.mesa tipo de mesa.

mesa Código identificador de la mesa.

mesas.fusionadas Mesas fusionadas.

nro.voto .

lista Lista política del candidato.

pacto Pacto político del candidato.

partido Partido político del candidato.

candidato Nombre del candidato.

votos Número total de votos.

Source

Los datos fueron obtenidos desde el servicio electoral de Chile (SERVEL) en el web <https://www.servel.cl>. El nombre del archivo era Resultados Primarias Presidenciales 2021 CHILE.xlsx, y fue descargado el 4 de octubre del 2022. Los datos fueron ordenados, y solo aquellas filas que contenían información en la columna 'votos' son parte de la dataframe.

Examples

```
data(primarias)
head(primarias)
table(primarias$region)
table(primarias$region,primarias$candidato)
tapply(primarias$votos,primarias$candidato,sum)
```

pspLlancahue

Ubicación cartesiana de árboles en el bosque de Llancahue para uso del libro.

Description

Corresponde a la posición cartesiana, especie, y diámetro de árboles en una parcela de muestreo en el bosque de Llancahue, cerca de Valdivia, Chile. La parcela es rectangular con dimensiones de 130 m por 70 m. Mayores antecedentes aparecen en las referencias.

Usage

```
data(pspLlancahue)
```

Format

Contains tree-level variables, as follows:

arb.id Identificador del árbol.

spp Codificación de la especie como sigue: AP= *Aextocicon punctatum*, EC=*Eucryphia cordifolia*, GA=*Gevuina avellana*, LP=*Laureliopsis philippiana*, LS=*Laurelia sempervirens*, ND=*Nothofagus dombeyi*, Ot=Other, PS=*Podocarpus saligna*.

dap Diámetro a la altura del pecho, en cm.

coord.x Posición cartesiana en el eje-X, en m.

coord.y Posición cartesiana en el eje-Y, en m.

Source

Los datos fueron cedidos por el Prof. Daniel Soto de Universidad de Aysen (Coyhaique, Chile).

References

- Soto DP, Salas C, Donoso PJ, Uteau D. 2010. Heterogeneidad estructural y espacial de un bosque mixto dominado por *Nothofagus dombeyi* después de un disturbio parcial. *Revista Chilena de Historia Natural* 83(3): 335-347.

Examples

```
data(pspLlancahue)
head(pspLlancahue)
descstat(pspLlancahue$dap)
boxplot(dap~spp, data=pspLlancahue)
```

pspruca

Tree spatial coordinates in the Rucamanque forest

Description

Tree-level variables and spatial coordinates in a permanent sample plot of 1 ha (100 x 100m) in the Rucamanque experimental forest, near Temuco, Chile.

Usage

```
data(pspruca)
```

Format

The data frame contains four variables for the standing-alive trees as follows:

tree.no tree number

species Species name, "N. obliqua" is *Nothofagus obliqua*, "Ap" is *Aexitocicum punctatum*, etc.

crown.class Crown class (1: superior, 2: intermediate, 3: inferior)

dbh diameter at breast-height, in cm

x.coord Cartesian position at the X-axis, in m

y.coord Cartesian position at the Y-axis, in m

Source

Data were provided by Dr Christian Salas-Eljatib (Universidad de Chile, Santiago, Chile).

References

Salas C, LeMay V, Nunez P, Pacheco P, and Espinosa A. 2006. Spatial patterns in an old-growth *Nothofagus obliqua* forest in south-central Chile. *Forest Ecology and Management* 231(1-3): 38-46.
[doi:10.1016/j.foreco.2006.04.037](https://doi.org/10.1016/j.foreco.2006.04.037)

Examples

```
data(pspruca)
head(pspruca)
table(pspruca$species)
```

pspruca2*Ubicación espacial de árboles en el bosque de Rucamanque*

Description

Medidas a nivel de árbol y coordenadas espaciales en un parcela de muestreo permanente de 1 ha (100 x 100m) en el bosque de Rucamanque, cerca de Temuco, Chile. Mayores antecedentes en las referencias.

Usage

```
data(pspruca2)
```

Format

Las columnas describen características de los árboles vivos en pie, como sigue:

arbol Número del árbol

especie Nombre de la especie, "N. obliqua" es *Nothofagus obliqua*, "Ap" es *Aexitocicum punctatum*, etc.

clase.copa Clase de copa (1: superior, 2: intermedio, 3: inferior)

dap Diámetro a la altura del pecho, en cm

coord.x Posicion cartesiana en el eje X, en m

coord.y Posicion cartesiana en el eje Y, en m

Source

Los datos fueron cedidos por el Dr Christian Salas-Eljatib (Santiago, Chile).

References

Salas C, LeMay V, Nunez P, Pacheco P, and Espinosa A. 2006. Spatial patterns in an old-growth *Nothofagus obliqua* forest in south-central Chile. *Forest Ecology and Management* 231(1-3): 38-46. [doi:10.1016/j.foreco.2006.04.037](https://doi.org/10.1016/j.foreco.2006.04.037)

Examples

```
data(pspruca2)
table(pspruca2$especie)
```

ptaeda

*Height growth of Pinus taeda (Loblolly pine) trees***Description**

The Loblolly data frame has 84 rows and tree columns of records of the tree height growth of Loblolly pine trees. This dataframe is a slight modification to the original dataframe "Loblolly" from the *datasets* R package.

Usage

```
data(ptaeda, package="datana")
```

Format

A dataframe containing the following columns:

seed.id an ordered factor indicating the seed source for the tree. The ordering is according to increasing maximum height.

age a numeric vector of tree ages, in yr.

toth a numeric vector of tree heights, in m.

Source

Pinheiro, J. C. and Bates, D. M. (2000) Mixed-effects Models in S and S-PLUS. Springer.

Examples

```
data(ptaeda, package="datana")
head(ptaeda)
plot(toth ~ age, data = subset(ptaeda, seed.id == 329),
     xlab = "Age (yr)", las = 1,
     ylab = "Height (m)")
```

ptaeda2

*Crecimiento en altura de Pinus taeda***Description**

Esta dataframe contiene 84 folas y tres columnas de crecimiento en altura de árboles de Pinus taeda (Loblolly pine). Es una modificación de la dataframe "Loblolly" del paquete 'datasets' de R.

Usage

```
data(ptaeda2)
```

Format

Los datos contienen las siguientes columnas:

semilla.id Un factor indicando el origen de la semilla del árbol.

edad Edad del árbol, en años.

atot Altura total, en m.

Source

Pinheiro, J. C. and Bates, D. M. (2000) Mixed-effects Models in S and S-PLUS. Springer.

Examples

```
data(ptaeda2, package="datana")
head(ptaeda2)
plot(atot ~ edad, data = subset(ptaeda2, semilla.id == 329),
     xlab = "Edad (años)", las = 1,
     ylab = "Altura (m)")
```

pvalt

Obtain the P-value for a Standard t-distributed random variable

Description

Function to compute the P-value for a Standard t-distributed random variable.

Usage

```
pvalt(t.value, df, decnum = 14)
```

Arguments

t.value	A numeric random variable following a t-student pdf distribution.
df	degrees of freedom of the random variable following a t-student pdf distribution.
decnum	the number of decimals to be used in the output. The default is set to 5.

Details

It is suited to compute the P-value for any random variable following a Standard t probability density function (pdf). For instance, to obtain the p-value in a t-test.

Value

The function returns the P-value or probability of getting a value as large as t.value.

Author(s)

Christian Salas-Eljatib

Examples

```
# Load dataset
df <- datana::fertiliza2
head(df)
## Computes the t-test statistics (from the 'stats' package)
t.value <- stats::t.test(df$vol)
t.value
t.v <- as.numeric(t.value$statistic);t.v
deg.f <- as.numeric(t.value$parameter);deg.f

## Obtaining the p ##  pvalt(t.v,deg.f)
```

pvalz

*Obtain the P-value for a Standard Gaussian random variable***Description**

Function to computes the P-value for a Standard Gaussian random variable.

Usage

```
pvalz(zval, decnum = 5)
```

Arguments

zval	A numeric random variable following a Standard Gaussian distribution.
decnum	the number of decimals to be used in the output. The default is set to 5.

Details

It is suited to compute the P-value for any random variable following a Standard Gaussian probability density function.

Value

This function returns the P-value or probability of getting a value as large as 'zval'.

Author(s)

Christian Salas-Eljatib

Examples

```
pvalz(1.96)
```

rainfallCA	<i>Datos de precipitación en California</i>
------------	---

Description

Datos de precipitación medidos en distintos lugares de california, con las coordenadas de los puntos y su distancia a la costa.

Usage

```
data(rainfallCA)
```

Format

Este set de datos contiene las siguientes columnas:

saple.id Identificador del punto de muestreo.

easting Coordenada este del punto.

northing Coordenada norte del punto.

pp Precipitación, en pulgadas.

ele Elevación, en pies.

lat Latitud del punto.

d.coast Distancia a la costa, en millas.

Source

Los datos provienen de mediciones hechas en California

Examples

```
data(rainfallCA)
head(rainfallCA)
plot(pp~ele, data=rainfallCA)
hist(rainfallCA$pp)
```

`raulihg`*Height growth of Nothofagus alpina trees in Chile.*

Description

Time series data of height for rauli (*Nothofagus alpina*) trees in south-central Chile. These sampled trees are part of the ones used in Salas-Eljatib (2021, Ecological Applications). The full citation is provided below.

Usage

```
data(raulihg)
```

Format

The data frame contains four variables as follows:

tree.code tree id code

spp species common name

bha.t breast-height age, in yrs.

h.t total height, in m.

Source

Data were provided by Dr Christian Salas-Eljatib (Santiago, Chile).

References

- Salas-Eljatib C. 2021. An approach to quantify climate-productivity relationships: an example from a widespread *Nothofagus* forest. *Ecological Applications* 31(4): e02285. [doi:10.1002/eap.2285](https://doi.org/10.1002/eap.2285)
- Salas-Eljatib, C. 2021. Time series height-data for *Nothofagus alpina* trees. [doi:10.6084/m9.figshare.13521602.v5](https://doi.org/10.6084/m9.figshare.13521602.v5)

Examples

```
data(raulihg)
head(raulihg)
```

raulihg2*Crecimiento en altura de árboles de Nothofagus alpina.*

Description

Datos de series de tiempo de altura para árboles muestreados de *Nothofagus alpina* (raulí) en el centro-sur de Chile. Estos árboles son parte de los usados en Salas-Eljatib (2021, Ecological Applications). La cita completa se da en referencias.

Usage

```
data(raulihg2)
```

Format

Contiene variables de nivel individual, como se describen a continuacion::

tree.code Código del árbol

spp Nombre comun especie

bha.t Edad a la altura del pecho, en años.

h.t Altura total, en m.

Source

Datos cedidos por el Prof. Christian Salas-Eljatib.

References

- Salas-Eljatib C. 2021. An approach to quantify climate-productivity relationships: an example from a widespread *Nothofagus* forest. Ecological Applications 31(4): e02285. doi:10.1002/eap.2285
- Salas-Eljatib C. 2021. Time series height-data for *Nothofagus alpina* trees. doi:10.6084/m9.figshare.13521602.v5

Examples

```
data(raulihg2)
head(raulihg2)
```

`skew`*Computes the skewness of a numeric vector*

Description

The skewness is about the departure from symmetry of a frequency distribution. Therefore, It is about asymmetry. One way to assess asymmetry of a random variable is to compute an statistics representing its skewness. The current function an dimensionless statistics of the skewness of given vector.

Usage

```
skew(x, na.rm = TRUE)
```

Arguments

<code>x</code>	A numeric vector representing a random variable.
<code>na.rm</code>	Logical value to remove NA values. The default is set to TRUE.

Details

The skewness of a random variable is the third moment of the standardized variable. There are several ways of parameterizing an skewness estimator, such as depending on the third moment and the standard deviation of the random variable.

Value

The value of the the skewness of given vector

Author(s)

Christian Salas-Eljatib.

Examples

```
y.var<-rnorm(100);x.var<-rbeta(100,.2,2)
skew(y.var)
skew(x.var)
```

sludge	<i>Sludge data are at different cities, with a value of concentration zinc.</i>
--------	---

Description

Dataset contains 36 observations

Usage

```
data(sludge)
```

Format

Contains four variables, as follows:

city Name of city.

rate Concentration rate of sludge.

zinc Value of concentration (in ppm).

trt.comb Combination between city and rate factors.

Source

The data were provided from.. still remember.

References

not yet

Examples

```
data(sludge2)
table(sludge$city, sludge$rate)
levels(sludge$city)
tapply(sludge$zinc, list(sludge$city, sludge$rate), mean)
```

sludge2	<i>Sludge data are at different cities, with a value of concentration zinc.</i>
---------	---

Description

Datos de contenido de Zinc en el tratamiento de lodos

Usage

```
data(sludge2)
```

Format

Contiene las siguientes cuatro variables:

ciudad Nombre de la ciudad.

tasa Tasa de concentracion de lodo.

zinc Concentracion de Zinc, en ppm.

trt.comb Identificador de la combinacion de niveles entre los factores ciudad y tasa.

Source

The data were provided from.. still remember.

References

not yet

Examples

```
data(sludge2)
table(sludge2$ciudad, sludge2$tasa)
levels(sludge2$ciudad)
tapply(sludge2$zinc, list(sludge2$ciudad, sludge2$tasa), mean)
```

snaspe	<i>On the National System of State Protected Wild Areas (SNASPE) of Chile.</i>
--------	--

Description

Units of the National System of State Protected Wild Areas (SNASPE).

Usage

```
data(snaspe)
```

Format

Contains the following variables:

unit.id Number for the unit.

unit Name of the protected area.

category Category of the unit. It can be either a National Park, a National Reserve or a Natural Monument.

county Name of the county where the unit is located.

province Province where the unit is located.

region Region where the unit is located.

perim.km Perimeter, in km.

area.ha Area, in hectares.

area.m2 Area, in m².

Source

These data are freely available at <https://ide.minagri.gob.cl>

References

The Chilean SNASPE is under the direction of the Chilean Forest Service (CONAF). Further information and documentation can be found at <https://www.conaf.cl>

Examples

```
data(snaspe)
head(snaspe)
table(snaspe$category)
tapply(snaspe$area.ha, snaspe$category, mean)
```

snaspe2

Sistema nacional de areas protegidas del estado (SNASPE) de Chile

Description

Contiene variables general de las unidades del sistema de areas protegidas por el estado de Chile (SNASPE).

Usage

```
data(snaspe2)
```

Format

Contiene las siguientes variables para cada unidad del SNASPE:

uni.id Número indentificador de la unidad.

unidad Nombre de la unidad.

categoria Categoría de la unidad. Puede ser Parque Nacional, Reserva Nacional, o Monumento Natural.

comuna Nombre de la communa donde esta la unidad.

province Nombre de la provincia donde esta la unidad.

region Nombre de la región.

perim.km Perimetro, en km.

area.ha Área, en hectareas.

area.m2 Área, en m².

Source

Estos datos fueron obtenidos desde <https://ide.minagri.gob.cl>

References

EL SNASPE esta bajo la administración de la Corporación Nacional Forestal (CONAF) de Chile. Mayor información se puede encontrar en <https://www.conaf.cl>

Examples

```
data(snaspe2)
head(snaspe2)
table(snaspe2$categoria)
tapply(snaspe2$area.ha, snaspe2$categoria, mean)
```

soiltreat

Soil treatment experiment in tree seedlings

Description

A test was made of the effect of three soil treatments on the height growth of 2-year-old seedlings. Treatments were assigned at random to the three plots within each of 11 blocks. Each plot was made up of 50 seedlings. Average 5-year height growth was the criterion for evaluating treatments.

Usage

```
data(soiltreat)
```

Format

Contains the four following columns, at the plot-level,

block Block unit.

treat Treatment level.

ini.h Initial height, in m.

inc.h Increment in height during 5-year, in m.

Source

Table in page 71 of Freese (1967). The data were entered by Miss Nayeli Ramirez, a former student of Prof. Christian Salas-Eljatib.

References

- Freese, F 1967. Elementary statistical methods for foresters. Agriculture Handbook 3171, USDA Forest Service.

Examples

```
data(soiltreat)
head(soiltreat)
tapply(soiltreat$inc.h,soiltreat$treat,summary)
tapply(soiltreat$inc.h,soiltreat$treat,sd)
```

soiltreat2

*Tratamientos del suelo en el crecimiento de plantulas.***Description**

Un experimento sobre el efecto de tres tratamientos del suelo en el crecimiento en altura de plantulas de 2-años de edad. Los tratamientos fueron asignados aleatoriamente a tres parcelas dentro de cada uno de 11 bloques. Cada parcela esta constituida por hasta 50 plantulas. El promedio del incremento en altura de los últimos 5 años fue la variable de interes para evaluar los tratamientos.

Usage

```
data(soiltreat2)
```

Format

Los datos, a nivel de parcela, tienen las siguientes columnas,

bloque Bloque del experimento.

tmo Factor tratamiento, medido en tres niveles.

alt.ini Altura initial, rn m.

alt.inc Incremento en altura durante los últimos cinco años, en m.

Source

Cuadro de la página 71 de Freese (1967). Los datos fueron digitados por la Srta. Nayeli Ramirez, una estudiante del Prof. Christian Salas-Eljatib.

References

- Freese, F 1967. Elementary statistical methods for foresters. Agriculture Handbook 3171, USDA Forest Service.

Examples

```
data(soiltreat2)
head(soiltreat2)
tapply(soiltreat2$alt.inc,soiltreat2$tmo,summary)
tapply(soiltreat2$alt.inc,soiltreat2$tmo,sd)
```

spataustria	<i>Tree locations for several plots of Norway spruce (Picea abies) in Austria</i>
-------------	---

Description

The Austrian Research Center for Forests established a spacing experiment with Norway spruce (*Picea abies*) in the Vienna Woods. In the 'Hauersteig' experiment, several tree-level variables were measured within four sample plots over time. The current dataframe has only the measurements carried out in 1944.

Usage

```
data(spataustria)
```

Format

Contains cartesian position of trees, and covariates, in sample plots, as follows:

plot Plot number.

tree Tree number.

species Species code as follows: PCAB=*Picea abies*, LADC=*Larix decidua*, PNSY=*Pinus sylvestris*, FASY=*Fagus Sylvatica*, QCPE=*Quercus petraea*, BTPE=*Betula pendula*.

x.coord Cartesian position in the X-axis, in m.

y.coord Cartesian position in the Y-axis, in m.

year Measurement year.

dbh diameter at breast-height, in cm.

References

- Kindermann G, Kristofel F, Neumann M, Rossler G, Ledermann T & Schueler.
1. 109 years of forest growth measurements from individual Norway spruce trees. Sci. Data 5:180077 doi:[10.1038/sdata.2018.77](https://doi.org/10.1038/sdata.2018.77)

Examples

```
data(spataustria)
head(spataustria)
df<-spataustria
oldpar<-par(mar=c(4,4,0,0))
bord<-data.frame(
  x=c(min(df$x.coord),max(df$x.coord),min(df$x.coord),max(df$x.coord)),
  y=c(min(df$y.coord),min(df$y.coord),max(df$y.coord),min(df$y.coord))
)
plot(bord,type="n", xlab="x (m)", ylab="y (m)", asp=1, bty='n')
points(df$x.coord,df$y.coord,col=df$plot,cex=0.5)
par(oldpar)
```

tabtexdescstat	<i>Creates a LaTeX file having a descriptive statistics table for continuous variables</i>
----------------	--

Description

Function to create a LaTeX file for a table of descriptive statistics of continuous variables from a dataframe.

Usage

```
tabtexdescstat(
  data = data,
  colnames = colnames,
  varnames = varnames,
  cap = cap,
  nametab = nametab,
  save.file = FALSE,
  filename = "tabdescdata.tex",
  eng = TRUE,
  rowlab = "Variable",
  decnum = 3,
  font.size.tab = "footnotesize",
  font.type.tab = "normalfont"
)
```

Arguments

data	a dataframe containing numeric variables as columns.
colnames	a string having the column names of the dataframe to which the descriptive statistics will be computed.
varnames	a string having the name of each of the variables to be used in the LaTeX table.
cap	a string having the caption of the LaTeX table.
nametab	a string having a brief name to be used in both the label of the table and the file name. For instance, if "descdata", the table can be referred in your LaTeX document by using <code>\ref{tab:descdata}</code>
save.file	The default is set to "FALSE", if it is set to TRUE, then the option filename must be provided.
filename	A string having the name of the resulting LaTeX file having the table. The default is set to "tabdescdata.tex".
eng	The language to be used in the output. English is the default, meanwhile if eng=FALSE, Spanish is used.
rowlab	a character with the name to be used as label for the column where the variables will be printed. The default is set to "Variables".

decnum the number of decimals to be used in the output. The default is set to 3.
font.size.tab The defaults is set to "footnotesize".
font.type.tab The defaults is set to "normalfont".

Details

The resulting file is a LaTeX table, that can be added to your main LaTeX document by using `\input{filename}`.

Value

This function creates a LaTeX file having the following descriptive statistics: sample size, minimum, maximum, mean, median, SD, and coefficient of variation. If the full option is set to TRUE, the following statistics are added to the table: 25th and 75th percentiles, the interquartile range, skewness, and kurtosis.

Author(s)

Christian Salas-Eljatib.

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
df <- datana::idahohd
head(df)
##example 1
tabtexdescstat(data=df,nametab="idaho",
cap="Descriptive statistics table",
colnames=c("dbh","height"),varnames = c("Diameter","Height"))
##example 2
tabtexdescstat(data=df,nametab="idaho",
cap="Cuadro con estadística descriptiva",
colnames=c("dbh","height"),varnames = c("Diametro","Altura"),
eng=FALSE)
```

timeserplot

Produces a time series plot

Description

Produces a time series plot, of variable 'y' as a function of 'x' by an observational unit factor.

Usage

```
timeserplot(
  data = data,
  y = y,
  x = x,
  obs.unit = obs.unit,
  factor1 = NA,
  factor2 = NA,
  only.lines = FALSE,
  ylab = NA,
  xlab = NA,
  linetype.lab = NA,
  factor2.line = TRUE,
  factor2.col = FALSE,
  col.lines = "black",
  max.y.all = NA,
  levels.i.want = FALSE,
  col.lev.i.want = FALSE
)
```

Arguments

<code>data</code>	a dataframe with at least tree columns representing the response variable ("y"), the main predictor variable ("x"), and a variable indicating the observational unit ("obs.unit").
<code>y</code>	a character giving the column name of the response variable or variable of interest.
<code>x</code>	a character giving the column name of the main predictor variable. Generally this variable is time.
<code>obs.unit</code>	a character giving the column name containing the info of the observational unit.
<code>factor1</code>	an optional character having the name of a column having a factor variable (e.g., treatment). The default value is set to NULL.
<code>factor2</code>	an optional character having the name of a column having another factor variable (e.g., species). The default value is set to NULL.
<code>only.lines</code>	a logic value if only lines, but not including dots, are going to be drwan in the plot. The default value is set to FALSE.
<code>ylab</code>	Label for the Y-axis
<code>xlab</code>	Label for the X-axis
<code>linetype.lab</code>	is an optional string to be used as the title of the factor being represented by lines. It is only needed if factor1 and factor2 are defined. See example.
<code>factor2.line</code>	a logic value if the second factor, factor2, is going to be segregated according to the type of lines. The default value is set to TRUE.
<code>factor2.col</code>	a logic value if the second factor, factor2, is going to be segregated according to the color of the lines only. The default value is set to FALSE.
<code>col.lines</code>	A string specifying the single color to be used for the lines of the timeseries

max.y.all A number representing the maximum level of Y-axis for all classes
 levels.i.want A vector having the levels for the factor under study
 col.lev.i.want A vector having the colors to be used for the factor under study

Details

Both 'y' and 'x' must be numeric variables, and the column representing the observational unit, must be a factor. This factor identifies the longitudinal context of the data, for instance, a student being measured on time. Besides, two more factors can be added to the plotting details, in order to represent the potential variability among them.

Value

This function returns a time series plot

Note

Please, uses the function with caution, and run first the examples to understand it better.

Author(s)

Christian Salas-Eljatib

References

Salas-Eljatib, C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor, Santiago, Chile. 170 p. <https://eljatib.com/rlibro>

Examples

```
data(ficdiamgr, package="datana")
df <- ficdiamgr
head(df)
str(df)
df$site<-as.factor(df$site)
df$species<-as.factor(df$species)
table(df$tree,df$species)
table(df$species,df$site)
#
timeserplot(df, y="dbh", x="time", obs.unit = "tree")
timeserplot(df, y="dbh", x="time", obs.unit = "tree", only.lines = TRUE)
#
## Otros ejemplos de uso de la funcion
timeserplot(df, y="dbh", x="time", obs.unit = "tree", col.lines = "blue",
only.lines = TRUE)
timeserplot(df, y="dbh", x="time", obs.unit = "tree", only.lines = FALSE)
#
timeserplot(df, y="dbh", x="time", obs.unit = "tree", factor1="site")
timeserplot(df, y="dbh", x="time", obs.unit = "tree", factor1="site",
factor2= "species")
timeserplot(df, y="dbh", x="time", obs.unit = "tree", factor1="site",
```

```
factor2= "species", factor2.col = TRUE, only.lines = TRUE)
```

treevol

Diameter, height and volume for Black Cherry Trees

Description

This data set provides measurements of the diameter, height and volume of timber in 31 felled black cherry trees. The records are a slight modification to the original dataframe "trees" from the *datasets* R package.

Usage

```
data(treevol)
```

Format

A data frame with 31 observations and three variables

dbh Diameter at breast height, in cm.

toth Total height, in m.

vtot Timber volume, in cubic meters.

Source

Ryan TA, Joiner BL, and Ryan BF. 1976. The Minitab Student Handbook. Duxbury Press.

Examples

```
pairs(treevol, panel = panel.smooth, main = "treevol dataframe")
plot(vtot ~ dbh, data = treevol, log = "xy")
coplot(log(vtot) ~ log(dbh) | toth, data = treevol,
       panel = panel.smooth)
summary(m1 <- lm(log(vtot) ~ log(dbh), data = treevol))
summary(m2 <- update(m1, ~ . + log(toth), data = treevol))
anova(m1,m2)
```

treevol2

*Volumen, altura, y diámetro para árboles de Black Cherry***Description**

Estos datos provienen de mediciones de volumen, altura y diámetro en 31 árboles volteados de black cherry (*Prunus serotina*). Son una modificación la dataframe 'trees' del paquete datasets de R.

Usage

```
data(treevol2)
```

Format

Datos con 31 observaciones y tres variables

dap diámetro a la altura del pecho, en cm

atot altural total, en m

vtot volumen total, en m³

Source

Ryan, T. A., Joiner, B. L. and Ryan, B. F. (1976) The Minitab Student Handbook. Duxbury Press.

Examples

```
pairs(treevol2, panel = panel.smooth, main = "treevol dataframe")
plot(vtot ~ dap, data = treevol2, log = "xy")
coplot(log(vtot) ~ log(dap) | atot, data = treevol2,
       panel = panel.smooth)
summary(m1 <- lm(log(vtot) ~ log(dap), data = treevol2))
summary(m2 <- update(m1, ~ . + log(atot), data = treevol2))
anova(m1, m2)
```

treevolroble

*Tree volume of roble (Nothofagus obliqua) in the Rucamanque forest***Description**

These are tree-level measurement data of sample trees in the Rucamanque experimental forest, near Temuco, in the Araucania region in south-central Chile, measured in 1999. The data are the same as in the dataframe "treevolruca", but only having observations for the species *Nothofagus obliqua* (roble).

Usage

```
data(treevolroble)
```

Format

Contains tree-level variables, as follows:

tree.no Tree id
dbh Diameter at breast height, in cm
toth Total height, in m.
d6 Upper-stem diameter at 6 m, in cm
totv Tree gross volume, in m³ with bark.

Source

The data are provided courtesy of Dr Christian Salas at the Universidad de Chile (Santiago, Chile).

References

- Salas C. 2002. Ajuste y validación de ecuaciones de volumen para un relicto del bosque de Roble-Laurel-Lingue. Bosque 23(2): 81-92. doi:10.4067/S0717920020020000200009 https://eljatib.com/publication/2002-07-01_ajuste_y_validacion/

Examples

```
data(treevolroble)
head(treevolroble)
```

treevolroble2	<i>Volumen a nivel de árbol para roble (Nothofagus obliqua) especie en el bosque de Rucamanque</i>
---------------	--

Description

Volumen, altura y diámetro, entre otras para árboles muestra de Nothofagus obliqua (roble) en el bosque de Rucamanque, cerca de Temuco, en la región de la Araucanía, en el sur de Chile.

Usage

```
data(treevolroble2)
```

Format

Las siguientes columnas son parte de la dataframe:

arbol Número del árbol.

especie Especie.

dap Diámetro a la altura del pecho, en cm.

atot Altura total, en m.

d6 Diámetro fustal a los 6 m, en cm.

vtot Volumen bruto total, en m³ with bark.

Source

Los datos son proporcionados por el Prof. Christian Salas (Universidad de Chile).

References

- Salas C. 2002. Ajuste y validación de ecuaciones de volumen para un relicto del bosque de Roble-Laurel-Lingue. Bosque 23(2): 81-92. doi:10.4067/S07179200200200009 https://eljatib.com/publication/2002-07-01_ajuste_y_validacion/

Examples

```
data(treevolroble2)
head(treevolroble2)
```

xyboxplot

Function for building a scatterplot with superposing boxplots

Description

The function creates a scatterplot with superposing boxplots for the Y-axis variable. To a scatterplot between a response variable 'y' and a predictor variable 'x', this function superposes boxplots of the response by groups of the predictor variable. The main aim of the above described graph is to get a sense of the distribution of the response variable depending upon the predictor variable.

Usage

```
xyboxplot(
  x = x,
  y = y,
  col.dots = "blue",
  xlab = NULL,
  ylab = NULL,
  try.x.ascategory = FALSE,
  transp.dots = 0.2,
  transp.bbox = 0.1
)
```

Arguments

<code>x</code>	A numeric vector representing the X-axis variable.
<code>y</code>	A numeric vector representing the Y-axis variable (response).
<code>col.dots</code>	A string specifying the dot colors. The default is set to "blue".
<code>xlab</code>	(optional) A string specifying X-axis label.
<code>ylab</code>	(optional) A string specifying Y-axis label.
<code>try.x.ascategory</code>	A logical statement, if set to TRUE, the X-axis variable will be treated as categorical for the drawing of the boxplots. The default is set to FALSE.
<code>transp.dots</code>	A numeric value to be used as transparency for the dots of the figure to be produced. The default is set to 0.2
<code>transp.boxp</code>	A numeric value to be used as transparency for the boxplot of the figure to be produced. The default is set to 0.1

Details

Notice that the superposing boxplots for the Y-axis variable are computed by grouping the X-axis variable in 10 classes. Those classes are set by computing the ten percentiles of the X-axis variable, therefore each group has the same number of observations.

Value

The function returns the above described graph.

Author(s)

Christian Salas-Eljatib

References

- Salas-Eljatib C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor. Santiago, Chile. 170 p. <https://eljatib.com>
- Salas C, Stage AR, and Robinson AP. 2008. Modeling effects of overstory density and competing vegetation on tree height growth. Forest Science 54(1):107-122. doi:10.1093/forestscience/54.1.107

Examples

```
df <- datana::fishgrowth
xyboxplot(x=df$length,y=df$scale)
xyboxplot(x=df$length,y=df$scale,col.dots = "red",
xlab="Variable X")
xyboxplot(x=df$length,y=df$scale,xlab="Variable X")
xyboxplot(x=df$length,y=df$scale,xlab="Variable X",
transp.dots = 0.4)
xyboxplot(x=df$age,y=df$length,try.x.ascategory = TRUE)
```

xyhist

*A scatterplot with marginal histograms***Description**

The function produces a scatterplot between the 'y'-axis variable and the 'x'-axis variable, but also adding the marginal histograms for both variables.

Usage

```
xyhist(
  x = x,
  y = y,
  col.x = "blue",
  col.y = "red",
  xlab = NULL,
  ylab = NULL,
  x.lim = NULL,
  y.lim = NULL
)
```

Arguments

<code>x</code>	A numeric vector representing the X-axis variable
<code>y</code>	A numeric vector representing the Y-axis variable
<code>col.x</code>	(optional) A string specifying the color of the histogram of the X-variable. Default is "blue".
<code>col.y</code>	(optional) A string specifying the color of the histogram of the Y-variable. Default is "red".
<code>xlab</code>	(optional) A string specifying X-axis label. Default is "xvar".
<code>ylab</code>	(optional) A string specifying Y-axis label. Default is "yvar".
<code>x.lim</code>	(optional) A vector of two elements with the limits of the Y-axis. Default is the range of the X-variable.
<code>y.lim</code>	(optional) A vector of two elements with the limits of the Y-axis. Default is the range of the Y-variable.

Details

Both the response variable (Y-axis) and the predictor variable (X-axis) must be numeric.

Value

The function returns the above described graph.

Author(s)

Christian Salas-Eljatib

References

- Salas-Eljatib C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor. Santiago, Chile. <https://eljatib.com>

Examples

```
data(treevolroble)
df <- datana::treevolroble
head(df)
xyhist(x=df$dbh,y=df$toth)
xyhist(x=df$dbh,y=df$toth, xlab="Variable X", ylab="Variable Y")
xyhist(x=df$dbh,y=df$toth, xlab="Variable X", ylab="Variable Y",
       col.x = "gray",col.y="white")
```

xymultiplot

*Figure of a matrix of scatterplots and histograms for several variables.***Description**

The function produces a panel of multiple scatterplots and histograms, showing the correlation coefficient among all pairs of variables. Notice that the data must contain only numeric variables.

Usage

```
xymultiplot(
  x,
  smooth = TRUE,
  scale = FALSE,
  density = TRUE,
  digits = 2,
  method = "pearson",
  pch = 20,
  lm = FALSE,
  cor = TRUE,
  jiggle = FALSE,
  factor = 2,
  col.hist = "cyan",
  col.densi.curve = "black",
  show.points = TRUE,
  col.points = "gray",
  smoother = FALSE,
  col.smooth = "red",
  ellipses = FALSE,
```

```

    col.ellip = "blue",
    col.cent.point = "green",
    rug = TRUE,
    breaks = "Sturges",
    cex.cor = 1,
    ci = FALSE,
    alpha = 0.05,
    ...
)

```

Arguments

<code>x</code>	is a dataframe containing all the numeric variables to be used for drawing the panel plot
<code>smooth</code>	a logical value for drawing smooth curves. The default is set to TRUE.
<code>scale</code>	scales the correlation font by the size of the absolute correlation. The default is set to FALSE.
<code>density</code>	a logical value for drawing a density curve. The default is set to TRUE.
<code>digits</code>	an optional numeric value for the digits to be used for drawing the correlation coefficient in the panel. Defaults is set to 2.
<code>method</code>	a string giving the method to be used for computing the correlation coefficient. Default is set to "pearson".
<code>pch</code>	The plot character (The default is 20, which looks like '.').
<code>lm</code>	Plot the linear fit rather than the LOESS smoothed fits. The default is FALSE.
<code>cor</code>	If plotting regressions, should correlations be reported? The default is TRUE.
<code>jiggle</code>	Should the points be jittered before plotting? The default is FALSE.
<code>factor</code>	factor for jittering (1-5), therefore only needed if "jiggle" is set to TRUE.
<code>col.hist</code>	a string giving the color to be used for the histograms of the panel. Default is set to "cyan".
<code>col.densi.curve</code>	a string with the name of the color to be used for the density curve. The default is set to "black".
<code>show.points</code>	a logical value for drawing the points in the scatter-plots. Defaults is set to TRUE.
<code>col.points</code>	a string giving the color to be used for the data points. Default is set to "gray".
<code>smoother</code>	If TRUE, then smooth.scatter the data points-slow but pretty with lots of subjects
<code>col.smooth</code>	a string giving the color to be used for the smoothed curve of the scatterplot. Default is set to "red".
<code>ellipses</code>	an optional logical value for drawing an ellipse for the scatter-plots. The default is set to FALSE.
<code>col.ellip</code>	a string giving the color to be used for the ellipse of the scatterplot. The default is set to "blue".
<code>col.cent.point</code>	a string giving the color to be used for the centroid point of the ellipse of the scatterplot. The default is set to "blue".

<code>rug</code>	a logical value for drawing the rugs in the histograms. Defaults is set to TRUE.
<code>breaks</code>	a string giving the method to be used for obtaining the breaks of the histogram. Defaults is set to "Sturges".
<code>cex.cor</code>	If this is specified, this will change the size of the text in the correlations. this allows one to also change the size of the points in the plot by specifying the normal cex values. If just specifying cex, it will change the character size, if cex.cor is specified, then cex will function to change the point size.
<code>ci</code>	Draw confidence intervals for the linear model or for the loess fit, defaults to ci=FALSE. If confidence intervals are not drawn, the fitting function is lowess.
<code>alpha</code>	an optional numeric value for the significance level. Defaults is set to 0.05.
<code>...</code>	other graphical parameters (see par and section 'Details' below).

Details

Generates a multipanel (matrix) of scatterplots and histograms to explore potential relationships among variables.

Value

This function returns a multipanel of scatterplots and histograms

Author(s)

A modification of Christian Salas-Eljatib of the function `pairs.panels` of the package *psych*.

References

- Salas-Eljatib C. 2021. Análisis de datos con el programa estadístico R: una introducción aplicada. Ediciones Universidad Mayor. Santiago, Chile. <https://eljatib.com>

Examples

```
##First example
data(bears2)
head(bears2)
df <- bears2[,c('peso', 'edad', 'cabezaL', 'cabezaA', 'largo', 'pechoP')]
descstat(df)
xymultiplot(df)
xymultiplot(df, ellipse=TRUE)
xymultiplot(df, ellipses=TRUE, col.cent.point = "yellow",
  col.densi.curve = "dark green", col.hist = "white")
```

Index

* datasets

aboutrsq, [4](#)
aboutrsq2, [5](#)
airnyc, [6](#)
airnyc2, [7](#)
annualppCities, [8](#)
annualppCities2, [8](#)
bears, [9](#)
bears2, [10](#)
bearsdepu, [11](#)
bearsdepu2, [12](#)
beetles, [13](#)
beetles2, [14](#)
cameratrap, [15](#)
cameratrap2, [16](#)
carAccidents, [17](#)
casen, [18](#)
chicksw, [20](#)
chicksw2, [21](#)
co2temp, [21](#)
corkoak, [26](#)
corkoak2, [27](#)
election, [31](#)
election2, [31](#)
eucaleaf, [32](#)
eucaleaf2, [33](#)
eucaleafAll, [34](#)
eucaleafAll2, [35](#)
fertiliza, [38](#)
fertiliza2, [38](#)
ficdiamgr, [39](#)
ficdiamgr2, [40](#)
fishgrowth, [42](#)
fishgrowth2, [43](#)
forestfire, [43](#)
forestfire2, [45](#)
gdpcap, [46](#)
hgrdfir, [48](#)
hgrdfir2, [49](#)

idahohd, [51](#)
idahohd2, [52](#)
landcover, [54](#)
landcover2, [55](#)
largetrees, [56](#)
largetrees2, [57](#)
lifexpect, [58](#)
llancahue, [59](#)
llancahue2, [60](#)
papersdocstu, [64](#)
presenceIce, [65](#)
president, [66](#)
primarias, [67](#)
pspllancahue, [68](#)
pspruca, [69](#)
pspruca2, [70](#)
ptaeda, [71](#)
ptaeda2, [71](#)
rainfallCA, [74](#)
raulihg, [75](#)
raulihg2, [76](#)
sludge, [78](#)
sludge2, [78](#)
snaspe, [79](#)
snaspe2, [80](#)
soiltreat, [81](#)
soiltreat2, [82](#)
spataustria, [83](#)
treevol, [88](#)
treevol2, [89](#)
treevolroble, [89](#)
treevolroble2, [90](#)

aboutrsq, [4](#)
aboutrsq2, [5](#)
airnyc, [6](#)
airnyc2, [7](#)
annualppCities, [8](#)
annualppCities2, [8](#)

- bears, [9](#)
- bears2, [10](#)
- bearsdepu, [11](#)
- bearsdepu2, [12](#)
- beetles, [13](#)
- beetles2, [14](#)
- cameratrapp, [15](#)
- cameratrapp2, [16](#)
- carAccidents, [17](#)
- casen, [18](#)
- cdf, [19](#)
- chicksw, [20](#)
- chicksw2, [21](#)
- co2temp, [21](#)
- contrast, [24](#)
- corkoak, [26](#)
- corkoak2, [27](#)
- deleteLeft, [28](#)
- deleteRight, [29](#)
- descstat, [30](#)
- election, [31](#)
- election2, [31](#)
- eucaleaf, [32](#)
- eucaleaf2, [33](#)
- eucaleafAll, [34](#)
- eucaleafAll2, [35](#)
- extractLeft, [36](#)
- extractRight, [37](#)
- fertiliza, [38](#)
- fertiliza2, [38](#)
- ficdiamgr, [39](#)
- ficdiamgr2, [40](#)
- findColumn.byname, [41](#)
- fishgrowth, [42](#)
- fishgrowth2, [43](#)
- forestfire, [43](#)
- forestfire2, [45](#)
- gdpcap, [46](#)
- gmean, [47](#)
- graphical parameters, [96](#)
- hgrdfir, [48](#)
- hgrdfir2, [49](#)
- hmean, [50](#)
- idahohd, [51](#)
- idahohd2, [52](#)
- kurto, [53](#)
- landcover, [54](#)
- landcover2, [55](#)
- largetrees, [56](#)
- largetrees2, [57](#)
- lifexpect, [58](#)
- llancahue, [59](#)
- llancahue2, [60](#)
- lrt, [61](#)
- lrt.glm, [62](#)
- moda, [63](#)
- papersdocstu, [64](#)
- par, [96](#)
- presenceIce, [65](#)
- president, [66](#)
- primarias, [67](#)
- pspLlancahue, [68](#)
- pspruca, [69](#)
- pspruca2, [70](#)
- ptaeda, [71](#)
- ptaeda2, [71](#)
- pvalt, [72](#)
- pvalz, [73](#)
- rainfallCA, [74](#)
- raulihg, [75](#)
- raulihg2, [76](#)
- skew, [77](#)
- sludge, [78](#)
- sludge2, [78](#)
- snaspe, [79](#)
- snaspe2, [80](#)
- soiltreat, [81](#)
- soiltreat2, [82](#)
- spataustria, [83](#)
- tabtexdescstat, [84](#)
- timeserplot, [85](#)
- treevol, [88](#)
- treevol2, [89](#)
- treevolroble, [89](#)
- treevolroble2, [90](#)

xyboxplot, [91](#)
xyhist, [93](#)
xymultiplot, [94](#)