

Package ‘oeli’

May 19, 2025

Type Package

Title Some Utilities for Developing Data Science Software

Version 0.7.3

Description A collection of general-purpose helper functions that I (and maybe others) find useful when developing data science software. Includes tools for simulation, data transformation, input validation, and more.

License GPL (>= 3)

Encoding UTF-8

Config/testthat/edition 3

RoxygenNote 7.3.2

Imports benchmarkme, checkmate, cli, ggplot2, hexSticker, R6, Rcpp, SimMultiCorrData, stats, tools, utils

LinkingTo Rcpp, RcppArmadillo, testthat

Suggests knitr, rmarkdown, testthat (>= 3.0.0), xml2

URL <https://github.com/loelschlaeger/oeli>,
<http://loelschlaeger.de/oeli/>

BugReports <https://github.com/loelschlaeger/oeli/issues>

NeedsCompilation yes

Author Lennart Oelschläger [aut, cre]

Maintainer Lennart Oelschläger <oelschlaeger.lennart@gmail.com>

Repository CRAN

Date/Publication 2025-05-19 14:50:02 UTC

Contents

check_correlation_matrix	3
check_covariance_matrix	4
check_list_of_lists	5
check_missing	6

check_numeric_vector	7
check_probability_vector	10
check_transition_probability_matrix	11
chunk_vector	12
correlated_regressors	13
cov_to_chol	15
ddirichlet_cpp	16
delete_columns_data.frame	17
Dictionary	18
diff_cov	21
dmvnorm_cpp	23
do.call_timed	24
dtnorm_cpp	25
dwishart_cpp	26
find_namespace_calls	28
function_arguments	29
function_body	29
function_defaults	30
group_data.frame	31
identical_structure	32
input_check_response	33
insert_matrix_column	34
insert_vector_entry	35
map_indices	36
match_arg	37
match_numerics	38
matrix_diagonal_indices	39
matrix_indices	40
merge_lists	41
package_logo	41
permutations	43
print_data.frame	43
print_matrix	45
quiet	46
round_data.frame	47
sample_correlation_matrix	48
sample_covariance_matrix	49
sample_transition_probability_matrix	50
simulate_markov_chain	50
split_vector_at	51
stationary_distribution	52
Storage	53
subsets	57
system_information	58
timed	59
try_silent	60
unexpected_error	61
user_confirm	61

<i>check_correlation_matrix</i>	3
variable_name	62
vector_occurrence	63
Index	64

check_correlation_matrix
<i>Check correlation matrix</i>

Description

These functions check whether the input fulfills the properties of a correlation matrix.

Usage

```
check_correlation_matrix(x, dim = NULL, tolerance = sqrt(.Machine$double.eps))

assert_correlation_matrix(
  x,
  dim = NULL,
  tolerance = sqrt(.Machine$double.eps),
  .var.name = checkmate::vname(x),
  add = NULL
)

test_correlation_matrix(x, dim = NULL, tolerance = sqrt(.Machine$double.eps))
```

Arguments

x	[any] Object to check.
dim	[integer(1)] The matrix dimension.
tolerance	[numeric(1)] A non-negative tolerance value.
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
add	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_matrix](#).

See Also

Other matrix helpers: [check_covariance_matrix\(\)](#), [check_transition_probability_matrix\(\)](#), [cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
M <- matrix(c(1, 0.9, 0.9, 0.9, 1, -0.9, 0.9, -0.9, 1), nrow = 3)
check_correlation_matrix(M)
test_correlation_matrix(M)
## Not run:
assert_correlation_matrix(M)

## End(Not run)
```

check_covariance_matrix

Check covariance matrix

Description

These functions check whether the input fulfills the properties of a covariance matrix.

Usage

```
check_covariance_matrix(x, dim = NULL, tolerance = sqrt(.Machine$double.eps))

assert_covariance_matrix(
  x,
  dim = NULL,
  tolerance = sqrt(.Machine$double.eps),
  .var.name = checkmate::vname(x),
  add = NULL
)

test_covariance_matrix(x, dim = NULL, tolerance = sqrt(.Machine$double.eps))
```

Arguments

x	[any] Object to check.
dim	[integer(1)] The matrix dimension.
tolerance	[numeric(1)] A non-negative tolerance value.

<code>.var.name</code>	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
<code>add</code>	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_matrix](#).

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_transition_probability_matrix\(\)](#), [cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
M <- matrix(c(1, 2, 3, 2, 1, 2, 3, 2, 1), nrow = 3)
check_covariance_matrix(M)
test_covariance_matrix(M)
## Not run:
assert_covariance_matrix(M)

## End(Not run)
```

check_list_of_lists	<i>Check list of lists</i>
---------------------	----------------------------

Description

These functions check whether the input is a list that contains list elements.

Usage

```
check_list_of_lists(x, len = NULL)

assert_list_of_lists(
  x,
  len = NULL,
  .var.name = checkmate::vname(x),
  add = NULL
)

test_list_of_lists(x, len = NULL)
```

Arguments

x	[any] Object to check.
len	[integer(1)] Exact expected length of x.
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
add	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_list](#).

See Also

Other list helpers: [merge_lists\(\)](#)

Examples

```
L <- list(list(1), list(2), 3)
check_list_of_lists(L)
test_list_of_lists(L)
## Not run:
assert_list_of_lists(L)

## End(Not run)
```

check_missing

Check missing formal argument

Description

These functions check whether a value was specified as an argument to a function.

Usage

```
check_missing(x)

assert_missing(x)

test_missing(x)
```

Arguments

x	[any] A formal argument.
---	-----------------------------

Value

TODO

See Also

Other package helpers: [Dictionary](#), [Storage](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
f <- function(x) {  
  check_missing(x)  
}  
f()  
  
g <- function(x) {  
  test_missing(x)  
}  
g()  
  
h <- function(x) {  
  assert_missing(x)  
}  
## Not run:  
h()  
  
## End(Not run)
```

check_numeric_vector	<i>Check numeric vector</i>
----------------------	-----------------------------

Description

These functions check whether the input is a numeric vector.

Usage

```
check_numeric_vector(  
  x,  
  lower = -Inf,  
  upper = Inf,  
  finite = FALSE,  
  any.missing = TRUE,  
  all.missing = TRUE,  
  len = NULL,  
  min.len = NULL,  
  max.len = NULL,
```

```

    unique = FALSE,
    sorted = FALSE,
    names = NULL,
    typed.missing = FALSE,
    null.ok = FALSE
)

assert_numeric_vector(
  x,
  lower = -Inf,
  upper = Inf,
  finite = FALSE,
  any.missing = TRUE,
  all.missing = TRUE,
  len = NULL,
  min.len = NULL,
  max.len = NULL,
  unique = FALSE,
  sorted = FALSE,
  names = NULL,
  typed.missing = FALSE,
  null.ok = FALSE,
  .var.name = checkmate::vname(x),
  add = NULL
)

test_numeric_vector(
  x,
  lower = -Inf,
  upper = Inf,
  finite = FALSE,
  any.missing = TRUE,
  all.missing = TRUE,
  len = NULL,
  min.len = NULL,
  max.len = NULL,
  unique = FALSE,
  sorted = FALSE,
  names = NULL,
  typed.missing = FALSE,
  null.ok = FALSE
)

```

Arguments

x	[any] Object to check.
lower	[numeric(1)]

	Lower value all elements of x must be greater than or equal to.
upper	[numeric(1)] Upper value all elements of x must be lower than or equal to.
finite	[logical(1)] Check for only finite values? Default is FALSE.
any.missing	[logical(1)] Are vectors with missing values allowed? Default is TRUE.
all.missing	[logical(1)] Are vectors with no non-missing values allowed? Default is TRUE. Note that empty vectors do not have non-missing values.
len	[integer(1)] Exact expected length of x.
min.len	[integer(1)] Minimal length of x.
max.len	[integer(1)] Maximal length of x.
unique	[logical(1)] Must all values be unique? Default is FALSE.
sorted	[logical(1)] Elements must be sorted in ascending order. Missing values are ignored.
names	[character(1)] Check for names. See checkNamed for possible values. Default is “any” which performs no check at all. Note that you can use checkSubset to check for a specific set of names.
typed.missing	[logical(1)] If set to FALSE (default), all types of missing values (NA, NA_integer_, NA_real_, NA_character_ or NA_character_) as well as empty vectors are allowed while type-checking atomic input. Set to TRUE to enable strict type checking.
null.ok	[logical(1)] If set to TRUE, x may also be NULL. In this case only a type check of x is performed, all additional checks are disabled.
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
add	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_numeric](#).

See Also

Other vector helpers: [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
x <- c(1, 2, "3")
check_numeric_vector(x)
test_numeric_vector(x)
## Not run:
assert_numeric_vector(x)

## End(Not run)
```

check_probability_vector

Check probability vector

Description

These functions check whether the input fulfills the properties of a probability matrix.

Usage

```
check_probability_vector(x, len = NULL, tolerance = sqrt(.Machine$double.eps))
```

```
assert_probability_vector(
  x,
  len = NULL,
  tolerance = sqrt(.Machine$double.eps),
  .var.name = checkmate::vname(x),
  add = NULL
)
```

```
test_probability_vector(x, len = NULL, tolerance = sqrt(.Machine$double.eps))
```

Arguments

x	[any] Object to check.
len	[integer(1)] Exact expected length of x.
tolerance	[numeric(1)] A non-negative tolerance value.
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
add	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_numeric](#).

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
p <- c(0.2, 0.3, 0.6)
check_probability_vector(p)
test_probability_vector(p)
## Not run:
assert_probability_vector(p)

## End(Not run)
```

`check_transition_probability_matrix`*Check transition probability matrix*

Description

These functions check whether the input is a transition probability matrix.

Usage

```
check_transition_probability_matrix(
  x,
  dim = NULL,
  tolerance = sqrt(.Machine$double.eps)
)

assert_transition_probability_matrix(
  x,
  dim = NULL,
  tolerance = sqrt(.Machine$double.eps),
  .var.name = checkmate::vname(x),
  add = NULL
)

test_transition_probability_matrix(
  x,
  dim = NULL,
  tolerance = sqrt(.Machine$double.eps)
)
```

Arguments

x	[any] Object to check.
dim	[integer(1)] The matrix dimension.
tolerance	[numeric(1)] A non-negative tolerance value.
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .
add	[AssertCollection] Collection to store assertion messages. See AssertCollection .

Value

Same as documented in [check_matrix](#).

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
T <- matrix(c(0.8, 0.2, 0.1, 0.1, 0.7, 0.4, 0.1, 0.1, 0.6), nrow = 3)
check_transition_probability_matrix(T)
test_transition_probability_matrix(T)
## Not run:
assert_transition_probability_matrix(T)

## End(Not run)
```

chunk_vector

Split a vector into chunks

Description

This function either

- splits a vector into n chunks of equal size (type = 1),
- splits a vector into chunks of size n (type = 2).

Usage

```
chunk_vector(x, n, type = 1, strict = FALSE)
```

Arguments

<code>x</code>	<code>[atomic()]</code> A vector of elements.
<code>n</code>	<code>[integer(1)]</code> A number smaller or equal <code>length(x)</code> .
<code>type</code>	<code>[1 2]</code> Either • 1 (default) to split <code>x</code> into <code>n</code> chunks of equal size, • or 2 to split <code>x</code> into chunks of size <code>n</code>.
<code>strict</code>	<code>[logical(1)]</code> Set to <code>TRUE</code> to fail if <code>length(x)</code> is not a multiple of <code>n</code> , or <code>FALSE</code> (default), else.

Value

A list.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
x <- 1:12
chunk_vector(x, n = 3, type = 1)
chunk_vector(x, n = 3, type = 2)
try(chunk_vector(x, n = 5, strict = TRUE))
```

`correlated_regressors` *Simulate correlated regressor values*

Description

This function simulates regressor values from various marginal distributions with custom correlations.

Usage

```
correlated_regressors(
  labels,
  n = 100,
  marginals = list(),
  correlation = diag(length(labels)),
  verbose = FALSE
)
```

Arguments

labels	[character()] Unique labels for the regressors.
n	[integer(1)] The number of values per regressor.
marginals	[list()] Optionally marginal distributions for regressors. If not specified, standard normal marginal distributions are used. Each list entry must be named according to a regressor label, and the following distributions are currently supported: discrete distributions • Poisson: <code>list(type = "poisson", lambda = ...)</code> • categorical: <code>list(type = "categorical", p = c(...))</code> continuous distributions • normal: <code>list(type = "normal", mean = ..., sd = ...)</code> • uniform: <code>list(type = "uniform", min = ..., max = ...)</code>
correlation	[matrix()] A correlation matrix of dimension <code>length(labels)</code> , where the (p, q)-th entry defines the correlation between regressor <code>labels[p]</code> and <code>labels[q]</code> .
verbose	[logical(1)] Print information about the simulated regressors?

Value

A data.frame with `n` rows and `length(labels)` columns.

References

This function heavily depends on the `{SimMultiCorrData}` package.

See Also

Other simulation helpers: `ddirichlet_cpp()`, `dmvnorm_cpp()`, `dtnorm_cpp()`, `dwishart_cpp()`, `simulate_markov_chain()`

Examples

```
labels <- c("P", "C", "N1", "N2", "U")
n <- 100
marginals <- list(
  "P" = list(type = "poisson", lambda = 2),
  "C" = list(type = "categorical", p = c(0.3, 0.2, 0.5)),
  "N1" = list(type = "normal", mean = -1, sd = 2),
  "U" = list(type = "uniform", min = -2, max = -1)
)
correlation <- matrix(
  c(1, -0.3, -0.1, 0, 0.5,
    -0.3, 1, 0.3, -0.5, -0.7,
    -0.1, 0.3, 1, -0.3, -0.3,
```

```

      0, -0.5, -0.3, 1, 0.1,
      0.5, -0.7, -0.3, 0.1, 1),
    nrow = 5, ncol = 5
  )
  data <- correlated_regressors(
    labels = labels, n = n, marginals = marginals, correlation = correlation
  )
  head(data)

```

cov_to_chol

Cholesky root of covariance matrix

Description

These functions compute the Cholesky root elements of a covariance matrix and, conversely, build a covariance matrix from its Cholesky root elements.

Usage

```
cov_to_chol(cov, unique = TRUE)
```

```
chol_to_cov(chol)
```

```
unique_chol(chol)
```

Arguments

cov	[matrix()] A covariance matrix. It can also be the zero matrix, in which case the Cholesky root is defined as the zero matrix.
unique	[logical(1)] Ensure that the Cholesky decomposition is unique by restricting the diagonal elements to be positive?
chol	[numeric()] Cholesky root elements.

Value

For [cov_to_chol](#) a numeric vector of Cholesky root elements.

For [chol_to_cov](#) a covariance matrix.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
cov <- sample_covariance_matrix(4)
chol <- cov_to_chol(cov)
all.equal(cov, chol_to_cov(chol))
```

ddirichlet_cpp	<i>Dirichlet distribution</i>
----------------	-------------------------------

Description

The function `ddirichlet()` computes the density of a Dirichlet distribution.

The function `rdirichlet()` samples from a Dirichlet distribution.

The functions with suffix `_cpp` perform no input checks, hence are faster.

Usage

```
ddirichlet_cpp(x, concentration, log = FALSE)
```

```
rdirichlet_cpp(concentration)
```

```
ddirichlet(x, concentration, log = FALSE)
```

```
rdirichlet(n = 1, concentration)
```

Arguments

<code>x</code>	[numeric()] A probability vector.
<code>concentration</code>	[numeric()] A concentration vector of the same length as <code>x</code> .
<code>log</code>	[logical(1)] Return the logarithm of the density value?
<code>n</code>	[integer(1)] The number of samples.

Value

For `ddirichlet()`: The density value.

For `rdirichlet()`: If `n = 1` a vector of length `p`, else a matrix of dimension `n` times `p` with samples as rows.

See Also

Other simulation helpers: [correlated_regressors\(\)](#), [dmvnorm_cpp\(\)](#), [dtnorm_cpp\(\)](#), [dwishart_cpp\(\)](#), [simulate_markov_chain\(\)](#)

Examples

```
x <- c(0.5, 0.3, 0.2)
concentration <- 1:3

# compute density
ddirichlet(x = x, concentration = concentration)
ddirichlet(x = x, concentration = concentration, log = TRUE)

# sample
rdirichlet(concentration = 1:3)
rdirichlet(n = 4, concentration = 1:2)
```

```
delete_columns_data.frame
```

Deleting data.frame columns

Description

This function deletes columns of a data.frame by name.

Usage

```
delete_columns_data.frame(df, column_names)
```

Arguments

df	[data.frame] A data.frame.
column_names	[character()] The name(s) of column(s) of df to delete.

Value

The input df without the columns defined by column_names.

See Also

Other data.frame helpers: [group_data.frame\(\)](#), [round_data.frame\(\)](#)

Examples

```
df <- data.frame("label" = c("A", "B"), "number" = 1:10)
delete_columns_data.frame(df = df, column_names = "label")
delete_columns_data.frame(df = df, column_names = "number")
delete_columns_data.frame(df = df, column_names = c("label", "number"))
```

Dictionary

*Dictionary R6 Object***Description**

Provides a simple key-value interface based on R6.

Active bindings

keys [character()]

Available keys.

alias [list()]

Available keys per alias value.

Methods**Public methods:**

- [Dictionary\\$new\(\)](#)
- [Dictionary\\$add\(\)](#)
- [Dictionary\\$get\(\)](#)
- [Dictionary\\$remove\(\)](#)
- [Dictionary\\$print\(\)](#)

Method `new()`: Initializing a new Dictionary object.

Usage:

```
Dictionary$new(
  key_name,
  alias_name = NULL,
  value_names = character(),
  value_assert = alist(),
  allow_overwrite = TRUE,
  keys_reserved = character(),
  alias_choices = NULL,
  dictionary_name = NULL
)
```

Arguments:

key_name [character(1)]

The name for the key variable.

alias_name [NULL | character(1)]

Optionally the name for the alias variable.

value_names [character(0)]

The names of the values connected to a key.

value_assert [alist(1)]
 For each element in `value_names`, `values_assert` *can* have an identically named element of the form `checkmate::assert*(...)`, where ... can be any argument for the assertion function except for the `x` argument.

allow_overwrite [logical(1)]
 Allow overwriting existing keys with new values? Duplicate keys are never allowed.

keys_reserved [character()]
 Names that must not be used as keys.

alias_choices [NULL or character()]
 Optionally possible values for the alias. Can also be NULL, then all alias values are allowed.

dictionary_name [NULL or character()]
 Optionally the name for the dictionary.

Method add(): Adding an element to the dictionary.

Usage:

```
Dictionary$add(...)
```

Arguments:

... Values for

- the key variable `key_name` (must be a single character),
- the alias variable `alias_name` (optionally, must then be a character vector),
- all the variables specified for `value_names` (if any, they must comply to the `value_assert` checks).

Method get(): Getting elements from the dictionary.

Usage:

```
Dictionary$get(key, value = NULL)
```

Arguments:

key [character(1)]

A value for the key variable `key_name`. Use the `$keys` method for available keys.

value [NULL | character(1)]

One of the elements in `value_names`, selecting the required value. Can also be NULL (default) for all values connected to the key, returned as a list.

Method remove(): Removing elements from the dictionary (and associated alias, if any).

Usage:

```
Dictionary$remove(key)
```

Arguments:

key [character(1)]

A value for the key variable `key_name`. Use the `$keys` method for available keys.

Method print(): Printing details of the dictionary.

Usage:

```
Dictionary$print()
```

See Also

Other package helpers: [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
# Managing variable metadata for a dataset
```

```
meta_dict <- Dictionary$new(
  key_name = "var_name",
  alias_name = "category",
  value_names = c("label", "type"),
  value_assert = alist(
    label = checkmate::assert_string(),
    type = checkmate::assert_choice(choices = c("numeric", "factor", "character"))
  ),
  allow_overwrite = FALSE,
  keys_reserved = c("id"),
  alias_choices = c("demographics", "outcome", "other"),
  dictionary_name = "Variable Metadata"
)
```

```
# Add entries to the dictionary
```

```
meta_dict$add(
  var_name = "age",
  label = "Age of respondent",
  type = "numeric",
  category = "demographics"
)
```

```
meta_dict$add(
  var_name = "gender",
  label = "Gender identity",
  type = "factor",
  category = "demographics"
)
```

```
meta_dict$add(
  var_name = "income",
  label = "Annual income in USD",
  type = "numeric",
  category = c("demographics", "outcome")
)
```

```
# Print dictionary
```

```
meta_dict$print()
```

```
# Retrieve full metadata for a variable
```

```
meta_dict$get("income")
```

```
# Retrieve a specific piece of metadata
```

```
meta_dict$get("income", value = "label")

# Show variables by category
meta_dict$alias
```

diff_cov

*Difference and un-difference covariance matrix***Description**

These functions difference and un-difference random vectors and covariance matrices.

Usage

```
diff_cov(cov, ref = 1)

undiff_cov(cov_diff, ref = 1)

delta(ref = 1, dim)

M(ranking = seq_len(dim), dim)
```

Arguments

cov, cov_diff	[matrix()] A (differenced) covariance matrix of dimension dim (or dim - 1, respectively).
ref	[integer(1)] The reference row between 1 and dim for differencing that maps cov to cov_diff, see details.
dim	[integer(1)] The matrix dimension.
ranking	[integer()] The integers 1 to dim in arbitrary order.

Details

Assume $x \sim N(0, \Sigma)$ is a multivariate normally distributed random vector of dimension n . We may want to consider the differenced vector

$$\tilde{x} = (x_1 - x_k, x_2 - x_k, \dots, x_n - x_k)',$$

excluding the k th element (hence, $\tilde{x}$ is of dimension $(n - 1) \times 1$). Formally, $\tilde{x} = \Delta_k x$, where Δ_k is a difference operator that depends on the reference row k . More precise, Δ_k is the identity matrix of dimension n without row k and with -1 s in column k . The difference operator Δ_k can be computed via `delta(ref = k, dim = n)`.

Then, $\tilde{x} \sim N(0, \tilde{\Sigma})$, where

$$\tilde{\Sigma} = \Delta_k \Sigma \Delta_k'$$

is the differenced covariance matrix with respect to row $k = 1, \dots, n$. The differenced covariance matrix $\tilde{\Sigma}$ can be computed via `diff_delta(Sigma, ref = k)`.

Since Δ_k is a non-bijective mapping, Σ cannot be uniquely restored from $\tilde{\Sigma}$. However, it is possible to compute a non-unique solution Σ_0 , such that $\Delta_k \Sigma_0 \Delta_k = \tilde{\Sigma}$. For such a non-unique solution, we add a column and a row of zeros at column and row number k to $\tilde{\Sigma}$, respectively. An "un-differenced" covariance matrix Σ_0 can be computed via `undiff_delta(Sigma_diff, ref = k)`.

As a alternative to Δ_k , the function `M()` returns a matrix for taking differences such that the resulting vector is negative.

Value

A (differenced or un-differenced) covariance matrix.

See Also

Other matrix helpers: `check_correlation_matrix()`, `check_covariance_matrix()`, `check_transition_probability_cov_to_chol()`, `insert_matrix_column()`, `matrix_diagonal_indices()`, `matrix_indices()`, `sample_correlation_matrix()`, `sample_covariance_matrix()`, `sample_transition_probability_matrix()`, `stationary_distribution()`

Examples

```
n <- 4
Sigma <- sample_covariance_matrix(dim = n)
k <- 2
x <- c(1, 3, 2, 4)

# build difference operator
delta_k <- delta(ref = k, dim = n)

# difference vector
delta_k %*% x

# difference Sigma
(Sigma_diff <- diff_cov(Sigma, ref = k))

# un-difference Sigma
(Sigma_0 <- undiff_cov(Sigma_diff, ref = k))

# difference again
Sigma_diff_2 <- diff_cov(Sigma_0, ref = k)
all.equal(Sigma_diff, Sigma_diff_2)

# difference such that the resulting vector is negative
M(ranking = order(x, decreasing = TRUE), dim = n) %*% x
```

dmvnorm_cpp

*Multivariate normal distribution***Description**

The function `dmvnorm()` computes the density of a multivariate normal distribution.

The function `rmvnorm()` samples from a multivariate normal distribution.

The functions with suffix `_cpp` perform no input checks, hence are faster.

The univariate normal distribution is available as the special case $p = 1$.

Usage

```
dmvnorm_cpp(x, mean, Sigma, log = FALSE)
```

```
rmvnorm_cpp(mean, Sigma, log = FALSE)
```

```
dmvnorm(x, mean, Sigma, log = FALSE)
```

```
rmvnorm(n = 1, mean, Sigma, log = FALSE)
```

Arguments

x	[numeric()] A quantile vector of length p.
mean	[numeric()] The mean vector of length p. For <code>dmvnorm()</code> and <code>rmvnorm()</code> , it can also be of length 1 for convenience, then <code>rep(mean, p)</code> is considered.
Sigma	[matrix()] The covariance matrix of dimension p. It can also be a zero matrix. For <code>rmvnorm()</code> , arbitrary dimensions (i.e., full rows and corresponding columns) of Sigma can be $\emptyset$. For <code>dmvnorm()</code> and <code>rmvnorm()</code> and if $p = 1$, it can also be a single numeric for convenience. Note that Sigma in this case is a variance, which is a different format than in <code>stats::dnorm()</code> or <code>stats::rnorm</code> , which require a standard deviation.
log	[logical(1)] For <code>dmvnorm()</code> : Return the logarithm of the density value? For <code>rmvnorm()</code> : Draw from a log-normal distribution?
n	[integer(1)] An integer, the number of requested samples.

Value

For `dmvnorm()`: The density value.

For `rmvnorm()`: If $n = 1$ a vector of length p (note that it is a column vector for `rmvnorm_cpp()`), else a matrix of dimension n times p with samples as rows.

See Also

Other simulation helpers: `correlated_regressors()`, `ddirichlet_cpp()`, `dtnorm_cpp()`, `dwishart_cpp()`, `simulate_markov_chain()`

Examples

```
x <- c(0, 0)
mean <- c(0, 0)
Sigma <- diag(2)

# compute density
dmvnorm(x = x, mean = mean, Sigma = Sigma)
dmvnorm(x = x, mean = mean, Sigma = Sigma, log = TRUE)

# sample
rmvnorm(n = 3, mean = mean, Sigma = Sigma)
rmvnorm(mean = mean, Sigma = Sigma, log = TRUE)
```

do.call_timed

Measure computation time

Description

This function measures the computation time of a call.

Usage

```
do.call_timed(what, args, units = "secs")
```

Arguments

what, args	Passed to <code>do.call</code> .
units	Passed to <code>difftime</code> .

Details

This function is a wrapper for `do.call`.

Value

A list of the two elements "result" (the results of the `do.call` call) and "time" (the computation time).

See Also

Other function helpers: `function_arguments()`, `function_body()`, `function_defaults()`, `quiet()`, `timed()`, `try_silent()`, `variable_name()`

Examples

```
## Not run:
what <- function(s) {
  Sys.sleep(s)
  return(s)
}
args <- list(s = 1)
do.call_timed(what = what, args = args)

## End(Not run)
```

dtnorm_cpp

Truncated normal distribution

Description

The function `dtnorm()` computes the density of a truncated normal distribution.

The function `rtnorm()` samples from a truncated normal distribution.

The function `dttnorm()` and `rttnorm()` compute the density and sample from a two-sided truncated normal distribution, respectively.

The functions with suffix `_cpp` perform no input checks, hence are faster.

Usage

```
dtnorm_cpp(x, mean, sd, point, above, log = FALSE)
```

```
dttnorm_cpp(x, mean, sd, lower, upper, log = FALSE)
```

```
rtnorm_cpp(mean, sd, point, above, log = FALSE)
```

```
rttnorm_cpp(mean, sd, lower, upper, log = FALSE)
```

```
dtnorm(x, mean, sd, point, above, log = FALSE)
```

```
dttnorm(x, mean, sd, lower, upper, log = FALSE)
```

```
rtnorm(mean, sd, point, above, log = FALSE)
```

```
rttnorm(mean, sd, lower, upper, log = FALSE)
```

Arguments

x	[numeric(1)] A quantile.
mean	[numeric(1)] The mean.
sd	[numeric(1)] The non-negative standard deviation.
point, lower, upper	[numeric(1)] The truncation point.
above	[logical(1)] Truncate from above? Else, from below.
log	[logical(1)] Return the logarithm of the density value?

Value

For dtnorm() and dtttnorm(): The density value.

For rtnorm() and rtttnorm(): The random draw

See Also

Other simulation helpers: [correlated_regressors\(\)](#), [ddirichlet_cpp\(\)](#), [dmvnorm_cpp\(\)](#), [dwishart_cpp\(\)](#), [simulate_markov_chain\(\)](#)

Examples

```
x <- c(0, 0)
mean <- c(0, 0)
Sigma <- diag(2)

# compute density
dmvnorm(x = x, mean = mean, Sigma = Sigma)
dmvnorm(x = x, mean = mean, Sigma = Sigma, log = TRUE)

# sample
rmvnorm(n = 3, mean = mean, Sigma = Sigma)
rmvnorm(mean = mean, Sigma = Sigma, log = TRUE)
```

dwishart_cpp

Wishart distribution

Description

The function `dwishart()` computes the density of a Wishart distribution.

The function `rwishart()` samples from a Wishart distribution.

The functions with suffix `_cpp` perform no input checks, hence are faster.

Usage

```
dwishart_cpp(x, df, scale, log = FALSE, inv = FALSE)

rwishart_cpp(df, scale, inv = FALSE)

dwishart(x, df, scale, log = FALSE, inv = FALSE)

rwishart(df, scale, inv = FALSE)
```

Arguments

x	[matrix()] A covariance matrix of dimension p.
df	[integer()] The degrees of freedom greater of equal p.
scale	[matrix()] The scale covariance matrix of dimension p.
log	[logical(1)] Return the logarithm of the density value?
inv	[logical(1)] Use this inverse Wishart distribution?

Value

For `dwishart()`: The density value.

For `rwishart()`: A matrix, the random draw.

See Also

Other simulation helpers: [correlated_regressors\(\)](#), [ddirichlet_cpp\(\)](#), [dmvnorm_cpp\(\)](#), [dtnorm_cpp\(\)](#), [simulate_markov_chain\(\)](#)

Examples

```
x <- diag(2)
df <- 4
scale <- diag(2)

# compute density
dwishart(x = x, df = df, scale = scale)
dwishart(x = x, df = df, scale = scale, log = TRUE)
dwishart(x = x, df = df, scale = scale, inv = TRUE)

# sample
rwishart(df = df, scale = scale)
rwishart(df = df, scale = scale, inv = TRUE)
```

find_namespace_calls	<i>Namespace calls</i>
----------------------	------------------------

Description

This function searches for namespace calls in .R files, i.e., code lines of the format <package name>::<function name>.

Usage

```
find_namespace_calls(path = "R", triple_colon = FALSE, as_list = FALSE)
```

Arguments

path	[character(1)] The path name to a folder. All .R files in this folder and sub-directories will be searched.
triple_colon	[logical(1)] Also search for :::?
as_list	[logical(1)] Simplify the output into a list of unique function names per package?

Value

A data.frame. If as_list = TRUE, a list.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
## Not run:  
find_namespace_calls()  
find_namespace_calls(as_list = TRUE)  
  
## End(Not run)
```

function_arguments	<i>Get function arguments</i>
--------------------	-------------------------------

Description

This function returns the names of function arguments.

Usage

```
function_arguments(f, with_default = TRUE, with_ellipsis = TRUE)
```

Arguments

f	[function] A function.
with_default	[logical(1)] Include function arguments that have default values?
with_ellipsis	[logical(1)] Include the "... " argument if present?

Value

A character vector.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_body\(\)](#), [function_defaults\(\)](#), [quiet\(\)](#), [timed\(\)](#), [try_silent\(\)](#), [variable_name\(\)](#)

Examples

```
f <- function(a, b = 1, c = "", ...) { }  
function_arguments(f)  
function_arguments(f, with_default = FALSE)  
function_arguments(f, with_ellipsis = FALSE)
```

function_body	<i>Extract function body</i>
---------------	------------------------------

Description

This function extracts the body of a function as a single character.

Usage

```
function_body(fun, braces = FALSE, nchar = getOption("width") - 4)
```

Arguments

fun	[function] A function.
braces	[logical(1)] Remove "{" and "}" at start and end (if any)?
nchar	[integer(1)] The maximum number of characters before abbreviation, at least 3.

Value

A character, the body of f.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_defaults\(\)](#), [quiet\(\)](#), [timed\(\)](#), [try_silent\(\)](#), [variable_name\(\)](#)

Examples

```
fun <- mean.default
function_body(fun)
function_body(fun, braces = TRUE)
function_body(fun, nchar = 30)
```

function_defaults	<i>Get default function arguments</i>
-------------------	---------------------------------------

Description

This function returns the default function arguments (if any).

Usage

```
function_defaults(f, exclude = NULL)
```

Arguments

f	[function] A function.
exclude	[NULL character()] Argument names to exclude. Can be NULL (default) to not exclude any argument names.

Value

A named list.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_body\(\)](#), [quiet\(\)](#), [timed\(\)](#), [try_silent\(\)](#), [variable_name\(\)](#)

Examples

```
f <- function(a, b = 1, c = "", ...) { }
function_defaults(f)
function_defaults(f, exclude = "b")
```

group_data.frame	<i>Grouping of a data.frame</i>
------------------	---------------------------------

Description

This function groups a data.frame according to values of one column.

Usage

```
group_data.frame(df, by, keep_by = TRUE)
```

Arguments

df	[data.frame] A data.frame.
by	[character(1)] The name of a column of df to group by.
keep_by	[logical(1)] Keep the grouping column by?

Value

A list of data.frames, subsets of df.

See Also

Other data.frame helpers: [delete_columns_data.frame\(\)](#), [round_data.frame\(\)](#)

Examples

```
df <- data.frame("label" = c("A", "B"), "number" = 1:10)
group_data.frame(df = df, by = "label")
group_data.frame(df = df, by = "label", keep_by = FALSE)
```

identical_structure	<i>Check if two objects have identical structure</i>
---------------------	--

Description

This function determines whether two objects have the same structure,

- which includes the `mode`, `class` and dimension
- but does *not* include concrete values or attributes.

Usage

```
identical_structure(x, y)
```

Arguments

x, y	[any] Two objects.
------	-----------------------

Value

Either TRUE if x and y have the same structure, and FALSE, else.

References

Inspired by <https://stackoverflow.com/a/45548885/15157768>.

See Also

Other package helpers: `Dictionary`, `Storage`, `check_missing()`, `find_namespace_calls()`, `input_check_response()`, `match_arg()`, `package_logo()`, `print_data.frame()`, `print_matrix()`, `system_information()`, `unexpected_error()`, `user_confirm()`

Examples

```
identical_structure(integer(1), 1L)
identical_structure(diag(2), matrix(rnorm(4), 2, 2))
identical_structure(diag(2), data.frame(diag(2)))
```

input_check_response *Standardized response to input check*

Description

This function provides a standardized response to input checks, ensuring consistency.

Usage

```
input_check_response(
  check,
  var_name = NULL,
  error = TRUE,
  prefix = "Input {.var {var_name}} is bad:"
)
```

Arguments

check	[TRUE character(1) list()] Matches the return value of the check* functions from the {checkmate} package, i.e., either TRUE if the check was successful, or a character (the error message) else. Can also be a list of multiple such values for alternative criteria, where at least one must be TRUE for a successful check.
var_name	[NULL character(1)] Optionally specifies the name of the input being checked. This name will be used for the default value of the prefix argument.
error	[logical(1)] If check is not TRUE (or no element in check is TRUE, if check is a list), throw an error?
prefix	[character(1)] A prefix for the thrown error message, only relevant if error is TRUE.

Value

TRUE if check is TRUE (or any element in check is TRUE, if check is a list). Else, depending on error:

- If error is TRUE, throws an error.
- If error is FALSE, returns FALSE.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```

x <- "1"
y <- 1

### check is successful
input_check_response(
  check = checkmate::check_character(x),
  var_name = "x",
  error = TRUE
)

### alternative checks
input_check_response(
  check = list(
    checkmate::check_character(x),
    checkmate::check_character(y)
  ),
  var_name = "x",
  error = TRUE
)

### standardized check response
## Not run:
input_check_response(
  check = checkmate::check_character(y),
  var_name = "y",
  error = TRUE
)

input_check_response(
  check = list(
    checkmate::check_flag(x),
    checkmate::check_character(y)
  ),
  var_name = "y",
  error = TRUE
)

## End(Not run)

```

insert_matrix_column *Insert column in matrix*

Description

This function inserts a column into a matrix.

Usage

```
insert_matrix_column(A, x, p)
```

Arguments

A	[matrix()] A matrix.
x	[atomic()] The column to be added, of length nrow(A). Can also be a single value.
p	[integer()] The position(s) where to add the column, one or more of: • $p = 0$ appends the column left • $p = \text{ncol}(A)$ appends the column right • $p = n$ inserts the column between the n-th and $(n + 1)$-th column of A.

Value

A matrix.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_matrix\(\)](#), [cov_to_chol\(\)](#), [diff_cov\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
A <- diag(3)
x <- 1:3
insert_matrix_column(A, x, 0)
insert_matrix_column(A, x, 1)
insert_matrix_column(A, x, 2)
insert_matrix_column(A, x, 3)

### also single value
x <- 2
insert_matrix_column(A, x, 0)

### also multiple positions
insert_matrix_column(A, x, 0:3)

### also trivial case
insert_matrix_column(matrix(nrow = 0, ncol = 0), integer(), integer())
```

insert_vector_entry *Insert entry in vector*

Description

This function inserts a value into a vector.

Usage

```
insert_vector_entry(v, x, p)
```

Arguments

v	[atomic()] A vector.
x	[atomic(1)] The entry to be added.
p	[integer()] The position(s) where to add the value, one or more of: • $p = 0$ appends the value left • $p = \text{length}(v)$ appends the value right • $p = n$ inserts the value between the n-th and $(n + 1)$-th entry of v.

Value

A vector.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
v <- 1:3
x <- 0
insert_vector_entry(v, x, 0)
insert_vector_entry(v, x, 1)
insert_vector_entry(v, x, 2)
insert_vector_entry(v, x, 3)

### also multiple positions
insert_vector_entry(v, x, 0:3)

### also trivial case
insert_vector_entry(integer(), integer(), integer())
```

map_indices

Map indices

Description

This function maps indices from an input vector to corresponding sequences of grouped indices. Each element from the input specifies a group to be mapped from the sequence, determined by the grouping size n .

Usage

```
map_indices(indices, n)
```

Arguments

indices	[integer()] An index vector, where each element specifies a group to be mapped from the sequence.
n	[integer] The size of each group of consecutive indices.

Details

This function is useful when working with indices arranged in fixed-size groups, where each group can be referenced by a single index. For example, if indices are structured in chunks of 3, calling this function with `n = 3` will map the corresponding groups of 3 consecutive indices for the given input indices, see the examples.

Value

An integer vector, containing the mapped indices according to the specified group size.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
# Example: Map indices based on groups of 3
map_indices(c(1, 3, 5), 3)
```

match_arg

Argument matching

Description

This function matches function arguments and is a modified version of [match.arg](#).

Usage

```
match_arg(arg, choices, several.ok = FALSE, none.ok = FALSE)
```

Arguments

arg	[character()] The function argument.
choices	[character()] Allowed values for arg.
several.ok	[logical(1)] Is arg allowed to have more than one element?
none.ok	[logical(1)] Is arg allowed to have zero elements?

Value

The un-abbreviated version of the exact or unique partial match if there is one. Otherwise, an error is signaled if `several.ok` is FALSE or `none.ok` is FALSE. When `several.ok` is TRUE and (at least) one element of `arg` has a match, all un-abbreviated versions of matches are returned. When `none.ok` is TRUE and `arg` has zero elements, `character(0)` is returned.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

match_numerics	<i>Best-possible match of two numeric vectors</i>
----------------	---

Description

This function matches the indices of two numeric vectors as good as possible (that means with the smallest possible sum of deviations).

Usage

```
match_numerics(x, y)
```

Arguments

x, y	[numeric()] Two vectors of the same length.
------	--

Value

An integer vector of length `length(x)` with the positions of `y` in `x`.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
x <- c(-1, 0, 1)
y <- c(0.1, 1.5, -1.2)
match_numerics(x, y)
```

matrix_diagonal_indices

Get indices of matrix diagonal

Description

This function returns the indices of the diagonal elements of a quadratic matrix.

Usage

```
matrix_diagonal_indices(n, triangular = NULL)
```

Arguments

n	[integer(1)] The matrix dimension.
triangular	[NULL or character(1)] If NULL (default), all elements of the matrix are considered. If "lower" ("upper"), only the lower- (upper-) triangular matrix is considered.

Value

An integer vector.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
# indices of diagonal elements
n <- 3
matrix(1:n^2, n, n)
matrix_diagonal_indices(n)

# indices of diagonal elements of lower-triangular matrix
L <- matrix(0, n, n)
L[lower.tri(L, diag=TRUE)] <- 1:((n * (n + 1)) / 2)
L
matrix_diagonal_indices(n, triangular = "lower")

# indices of diagonal elements of upper-triangular matrix
U <- matrix(0, n, n)
U[upper.tri(U, diag=TRUE)] <- 1:((n * (n + 1)) / 2)
U
matrix_diagonal_indices(n, triangular = "upper")
```

matrix_indices

*Get matrix indices***Description**

This function returns matrix indices as character.

Usage

```
matrix_indices(x, prefix = "", exclude_diagonal = FALSE)
```

Arguments

x	[matrix] A matrix.
prefix	[character(1)] A prefix for the indices.
exclude_diagonal	[logical(1)] Exclude indices where row equals column?

Value

A character vector.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
M <- diag(3)
matrix_indices(M)
matrix_indices(M, "M_")
matrix_indices(M, "M_", TRUE)
```

merge_lists

Merge named lists

Description

This function merges lists based on their element names. Elements are only included in the final output list, if no former list has contributed an element with the same name.

Usage

```
merge_lists(...)
```

Arguments

... One or more named list(s).

Value

A list.

See Also

Other list helpers: [check_list_of_lists\(\)](#)

Examples

```
merge_lists(list("a" = 1, "b" = 2), list("b" = 3, "c" = 4, "d" = NULL))
```

package_logo

Creating a basic logo for an R package

Description

This function creates a basic R package logo. The logo has a white background and the package name (with or without curly brackets) in the center. The font size for the package name is scaled such that it fits inside the logo. Type `?oeli` to see an example.

Usage

```
package_logo(  
  package_name,  
  brackets = FALSE,  
  background = ggplot2::ggplot() + ggplot2::theme_void(),  
  s_x = 1,  
  s_y = 1,  
  s_width = 1,  
  s_height = 1,  
  white_around_sticker = FALSE  
)
```

Arguments

package_name	[character(1)] The package name.
brackets	[logical(1)] Curly brackets around the package name?
background	A ggplot object, the background of the sticker.
s_x, s_y, s_width, s_height, white_around_sticker	Passed on to sticker .

Value

A ggplot object.

References

- This function builds upon [sticker](#).
- Use [use_logo](#) to set up the logo for a package.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
print(package_logo("my_package", brackets = TRUE))
```

`permutations`*Build permutations*

Description

This function creates all permutations of a given vector.

Usage

```
permutations(x)
```

Arguments

<code>x</code>	<code>[atomic()]</code> Any vector.
----------------	--

Value

A list of all permutations of `x`.

References

Modified version of <https://stackoverflow.com/a/20199902/15157768>.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
permutations(1:3)
permutations(LETTERS[1:3])
```

`print_data.frame`*Print (abbreviated) data.frame*

Description

This function prints a (possibly abbreviated) `data.frame`.

Usage

```
print_data.frame(
  x,
  rows = NULL,
  cols = NULL,
  digits = NULL,
  row.names = TRUE,
  col.names = TRUE
)
```

Arguments

x	[data.frame] A data.frame.
rows, cols	[integer(1) NULL] The number of rows or columns to be printed, greater or equal 2. Printing is abbreviated in the middle. Can be NULL to print everything.
digits	[integer(1) NULL] The number of decimal places to be used. Negative values are allowed, resulting in rounding to a power of ten. Can be NULL to not round.
row.names, col.names	[logical(1)] Print row names or column names?

Value

Invisibly returns x.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
x <- data.frame(1:10, LETTERS[1:10], stats::rnorm(10))
print_data.frame(x, rows = 7)
print_data.frame(x, rows = 7, cols = 2)
print_data.frame(x, rows = 7, cols = 2, digits = 1)
print_data.frame(x, rows = 7, cols = 2, digits = 1, row.names = FALSE)
print_data.frame(x, rows = 7, cols = 2, digits = 1, col.names = FALSE)
```

print_matrix	<i>Print (abbreviated) matrix</i>
--------------	-----------------------------------

Description

This function prints a (possibly abbreviated) matrix.

Usage

```
print_matrix(
  x,
  rowdots = 4,
  coldots = 4,
  digits = 2,
  label = NULL,
  simplify = FALSE,
  details = !simplify
)
```

Arguments

x	[atomic() matrix] The object to be printed.
rowdots	[integer(1)] The row number which is replaced by
coldots	[integer(1)] The column number which is replaced by
digits	[integer(1)] The number of printed decimal places if input x is numeric.
label	[character(1)] A label for x. Only printed if simplify = FALSE.
simplify	[logical(1)] Simplify the output?
details	[logical(1)] Print the type and dimension of x?

Value

Invisibly returns x.

References

This function is a modified version of pprint() from the {ramify} package.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
print_matrix(x = 1, label = "single numeric")
print_matrix(x = LETTERS[1:26], label = "letters")
print_matrix(x = 1:3, coldots = 2)
print_matrix(x = matrix(rnorm(99), ncol = 1), label = "single column matrix")
print_matrix(x = matrix(1:100, nrow = 1), label = "single row matrix")
print_matrix(x = matrix(LETTERS[1:24], ncol = 6), label = "big matrix")
print_matrix(x = diag(5), coldots = 2, rowdots = 2, simplify = TRUE)
```

quiet

Silence R code

Description

This function silences warnings, messages and any `cat()` or `print()` output from R expressions or functions.

Usage

```
quiet(x, print_cat = TRUE, message = TRUE, warning = TRUE)
```

Arguments

x	[expression] Any function or expression or value assignment expression.
print_cat	[logical(1)] Silence <code>print()</code> and <code>cat()</code> outputs?
message	[logical(1)] Silence messages?
warning	[logical(1)] Silence warnings?

Value

Invisibly the expression x.

References

This function is a modified version of [quiet](#).

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_body\(\)](#), [function_defaults\(\)](#), [timed\(\)](#), [try_silent\(\)](#), [variable_name\(\)](#)

Examples

```
f <- function() {
  warning("warning")
  message("message")
  cat("cat")
  print("print")
}
quiet(f())
```

round_data.frame	<i>Round numeric columns of a data.frame</i>
------------------	--

Description

This function rounds (only) the numeric columns of a data.frame.

Usage

```
round_data.frame(df, digits = 0)
```

Arguments

df	[data.frame] A data.frame.
digits	[integer(1) NULL] The number of decimal places to be used. Negative values are allowed, resulting in rounding to a power of ten. Can be NULL to not round.

Value

A data.frame.

See Also

Other data.frame helpers: [delete_columns_data.frame\(\)](#), [group_data.frame\(\)](#)

Examples

```
df <- data.frame("label" = c("A", "B"), "number" = rnorm(10))
round_data.frame(df, digits = 1)
```

sample_correlation_matrix

Sample correlation matrix

Description

This function samples a correlation matrix by sampling a covariance matrix from an inverse Wishart distribution and transforming it to a correlation matrix.

Usage

```
sample_correlation_matrix(dim, df = dim, scale = diag(dim))
```

Arguments

dim	[integer(1)] The dimension.
df	[integer(1)] The degrees of freedom of the inverse Wishart distribution greater or equal dim.
scale	[matrix()] The scale covariance matrix of the inverse Wishart distribution of dimension dim.

Value

A correlation matrix.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
sample_correlation_matrix(dim = 3)
```

sample_covariance_matrix
Sample covariance matrix

Description

This function samples a covariance matrix from an inverse Wishart distribution.

Usage

```
sample_covariance_matrix(dim, df = dim, scale = diag(dim), diag = FALSE)
```

Arguments

dim	[integer(1)] The dimension.
df	[integer(1)] The degrees of freedom of the inverse Wishart distribution greater or equal dim.
scale	[matrix()] The scale covariance matrix of the inverse Wishart distribution of dimension dim.
diag	[logical(1)] Diagonal matrix?

Value

A covariance matrix.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
sample_covariance_matrix(dim = 3)
```

sample_transition_probability_matrix

Sample transition probability matrices

Description

This function returns a random, squared matrix of dimension `dim` that fulfills the properties of a transition probability matrix.

Usage

```
sample_transition_probability_matrix(dim, state_persistent = TRUE)
```

Arguments

<code>dim</code>	[integer(1)] The dimension.
<code>state_persistent</code>	[logical(1)] Put more probability on the diagonal?

Value

A transition probability matrix.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [stationary_distribution\(\)](#)

Examples

```
sample_transition_probability_matrix(dim = 3)
```

simulate_markov_chain *Simulate Markov chain*

Description

This function simulates a Markov chain.

Usage

```
simulate_markov_chain(Gamma, T, delta = oeli::stationary_distribution(Gamma))
```

Arguments

Gamma	[matrix()] A transition probability matrix.
T	[integer(1)] The length of the Markov chain.
delta	[numeric()] A probability vector, the initial distribution. The stationary distribution is used by default.

Value

A numeric vector of length T with states.

See Also

Other simulation helpers: [correlated_regressors\(\)](#), [ddirichlet_cpp\(\)](#), [dmvnorm_cpp\(\)](#), [dtnorm_cpp\(\)](#), [dwishart_cpp\(\)](#)

Examples

```
Gamma <- matrix(c(0.8, 0.2, 0.3, 0.7), byrow = TRUE, nrow = 2)
delta <- c(0.6, 0.4)
simulate_markov_chain(Gamma = Gamma, T = 20, delta = delta)
```

split_vector_at	<i>Split a vector at positions</i>
-----------------	------------------------------------

Description

This function splits a vector at specific positions.

Usage

```
split_vector_at(x, at)
```

Arguments

x	[atomic()'] A vector of elements.
at	[integer()] Index position(s) just before to split. For example, at = n splits before the nth element of x.

Value

A list.

References

Based on <https://stackoverflow.com/a/19274414>.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [subsets\(\)](#), [vector_occurrence\(\)](#)

Examples

```
x <- 1:10
split_vector_at(x, c(2, 3, 5, 7))
```

stationary_distribution

Stationary distribution

Description

This function computes the stationary distribution corresponding to a transition probability matrix.

Usage

```
stationary_distribution(tpm, soft_fail = FALSE)
```

Arguments

tpm	[matrix()] A transition probability matrix.
soft_fail	[logical(1)] Return the discrete uniform distribution if the computation of the stationary distribution fails for some reason? Else, throw an error.

Value

A numeric vector.

See Also

Other matrix helpers: [check_correlation_matrix\(\)](#), [check_covariance_matrix\(\)](#), [check_transition_probability_cov_to_chol\(\)](#), [diff_cov\(\)](#), [insert_matrix_column\(\)](#), [matrix_diagonal_indices\(\)](#), [matrix_indices\(\)](#), [sample_correlation_matrix\(\)](#), [sample_covariance_matrix\(\)](#), [sample_transition_probability_matrix\(\)](#)

Examples

```
tpm <- matrix(0.05, nrow = 3, ncol = 3)
diag(tpm) <- 0.9
stationary_distribution(tpm)
```

Storage

*Storage R6 Object***Description**

Provides a simple indexing interface for list elements based on R6. Basically, it allows to store items in a list and to regain them based on identifiers defined by the user.

Value

The output depends on the method:

- `$new()` returns a Storage object.
- `$add()`, `$remove()`, and `$print()` invisibly return the Storage object (to allow for method chaining)
- `$get()` returns the requested element(s)
- `$number()` returns an integer
- `$indices()` return an integer vector

Setting identifiers

An identifier is a character, typically a binary property. Identifiers can be negated by placing an exclamation mark ("!") in front of them. Identifiers that have been assigned to other elements previously do not need to be specified again for new elements; instead, a default value can be used. This default value can be defined either globally for all cases (via the `$missing_identifier` field) or separately for each specific case (via the method argument).

User confirmation

If desired, the user can be asked for confirmation when adding, extracting, or removing elements using identifiers. This behavior can be set globally through the `$confirm` field or customized separately for each specific case via the method argument.

Active bindings

`identifier` [character()]

The identifiers used.

`confirm` [logical(1)]

The default value for confirmations.

`missing_identifier` [logical(1)]

The default value for not specified identifiers.

`hide_warnings` [logical(1)]

Hide warnings (for example if unknown identifiers are selected)?

Methods

Public methods:

- `Storage$new()`
- `Storage$add()`
- `Storage$get()`
- `Storage$remove()`
- `Storage$number()`
- `Storage$indices()`
- `Storage$print()`

Method `new()`: Initializing a Storage object.

Usage:

```
Storage$new()
```

Method `add()`: Adding an element.

Usage:

```
Storage$add(
  x,
  identifier,
  confirm = interactive() & self$confirm,
  missing_identifier = self$missing_identifier
)
```

Arguments:

`x` [any]

An object to be saved.

`identifier` [character()]

One or more identifiers (the identifier "all" is reserved to select all elements).

`confirm` [logical(1)]

Prompted for confirmation?

`missing_identifier` [logical(1)|NA]

The value for not specified identifiers.

Method `get()`: Getting elements.

Usage:

```
Storage$get(
  identifier = character(),
  ids = integer(),
  logical = "and",
  confirm = interactive() & self$confirm,
  missing_identifier = self$missing_identifier,
  id_names = FALSE
)
```

Arguments:

`identifier` [character()]

One or more identifiers (the identifier "all" is reserved to select all elements).

```
ids [integer()]
  One or more ids.
logical [character(1)]
  In the case that multiple identifiers are selected, how should they be combined? Options
  are:
  • "and" (the default): the identifiers are combined with logical and (all identifiers must be
    TRUE)
  • "or": the identifiers are combined with logical or (at least one identifier must be TRUE)
confirm [logical(1)]
  Prompted for confirmation?
missing_identifier [logical(1) | NA]
  The value for not specified identifiers.
id_names [logical(1)]
  Name the elements according to their ids?
```

Method `remove()`: removing elements

Usage:

```
Storage$remove(
  identifier = character(),
  ids = integer(),
  logical = "and",
  confirm = interactive() & self$confirm,
  missing_identifier = self$missing_identifier,
  shift_ids = TRUE
)
```

Arguments:

```
identifier [character()]
  Pn or more identifiers (the identifier "all" is reserved to select all elements).
ids [integer()]
  One or more ids.
logical [character(1)]
  In the case that multiple identifiers are selected, how should they be combined? Options
  are:
  • "and" (the default): the identifiers are combined with logical and (all identifiers must be
    TRUE)
  • "or": the identifiers are combined with logical or (at least one identifier must be TRUE)
confirm [logical(1)]
  Prompted for confirmation?
missing_identifier [logical(1) | NA]
  The value for not specified identifiers.
shift_ids [logical(1)]
  Shift ids when in-between elements are removed?
```

Method `number()`: Computing the number of identified elements.

Usage:

```
Storage$number(
  identifier = "all",
  missing_identifier = self$missing_identifier,
  logical = "and",
  confirm = FALSE
)
```

Arguments:

identifier [character()]

One or more identifiers (the identifier "all" is reserved to select all elements).

missing_identifier [logical(1) | NA]

The value for not specified identifiers.

logical [character(1)]

In the case that multiple identifiers are selected, how should they be combined? Options are:

- "and" (the default): the identifiers are combined with logical and (all identifiers must be TRUE)
- "or": the identifiers are combined with logical or (at least one identifier must be TRUE)

confirm [logical(1)]

Prompted for confirmation?

Method indices(): Returning indices based on defined identifiers.

Usage:

```
Storage$indices(
  identifier = "all",
  logical = "and",
  confirm = interactive() & self$confirm
)
```

Arguments:

identifier [character()]

One or more identifiers (the identifier "all" is reserved to select all elements).

logical [character(1)]

In the case that multiple identifiers are selected, how should they be combined? Options are:

- "and" (the default): the identifiers are combined with logical and (all identifiers must be TRUE)
- "or": the identifiers are combined with logical or (at least one identifier must be TRUE)

confirm [logical(1)]

Prompted for confirmation?

Method print(): Printing details of the saved elements.

Usage:

```
Storage$print(...)
```

Arguments:

... Currently not used.

See Also

Other package helpers: [Dictionary](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
### 1. Create a `Storage` object:
my_storage <- Storage$new()

# 2. Add elements along with identifiers:
my_storage$
  add(42, c("number", "rational"))$
  add(pi, c("number", "!rational"))$
  add("fear of black cats", c("text", "!rational"))$
  add("wearing a seat belt", c("text", "rational"))$
  add(mean, "function")

# 3. What elements are stored?
print(my_storage)

# 4. Extract elements based on identifiers:
my_storage$get("rational")
my_storage$get("!rational")
my_storage$get(c("text", "!rational"))
my_storage$get("all") # get all elements
my_storage$get(c("text", "!text"))
my_storage$get(c("text", "!text"), logical = "or")

# 5. Extract elements based on ids:
my_storage$get(ids = 4:5)
my_storage$get(ids = 4:5, id_names = TRUE) # add the ids as names
```

subsets

*Generate vector subsets***Description**

This function generates subsets of a vector.

Usage

```
subsets(v, n = seq_along(v))
```

Arguments

v	[atomic()'] A vector of elements.
n	[integer(1)'] The requested subset sizes.

Value

A list, each element is a subset of v.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [vector_occurrence\(\)](#)

Examples

```
v <- 1:3
subsets(v)
subsets(v, c(1, 3)) # only subsets of length 1 or 3
subsets(integer()) # trivial case works
```

system_information	<i>General system level information</i>
--------------------	---

Description

This function returns a list of general system level information.

Usage

```
system_information()
```

Value

A list with elements:

- `maschine`, the model name of the device
- `cores`, the number of cores
- `ram`, the size of the RAM
- `os`, the operating system
- `rversion`, the R version used

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [unexpected_error\(\)](#), [user_confirm\(\)](#)

Examples

```
system_information()
```

timed	<i>Interrupt long evaluations</i>
-------	-----------------------------------

Description

This function interrupts an evaluation after a certain number of seconds. Note the limitations documented in [setTimeLimit](#).

Usage

```
timed(expression, seconds = Inf, on_time_out = "silent")
```

Arguments

expression	[expression] An R expression to be evaluated.
seconds	[numeric(1)] The number of seconds.
on_time_out	[character(1)] Defines what action to take if the evaluation time exceeded, either: • "error" to throw an error exception • "warning" to return NULL along with a warning • "silent" (the default) to just return NULL

Value

The value of expression or, if the evaluation time exceeded, whatever is specified for on_time_out.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_body\(\)](#), [function_defaults\(\)](#), [quiet\(\)](#), [try_silent\(\)](#), [variable_name\(\)](#)

Examples

```
foo <- function(x) {  
  for (i in 1:10) Sys.sleep(x / 10)  
  return(x)  
}  
timed(foo(0.5), 1)  
timed(foo(1.5), 1)
```

try_silent	<i>Try an expression silently</i>
------------	-----------------------------------

Description

This function tries to execute `expr` and returns a string with the error message if the execution failed.

Usage

```
try_silent(expr)
```

Arguments

<code>expr</code>	[expression] An R expression to be evaluated.
-------------------	--

Details

This function is a wrapper for [try](#).

Value

Either the value of `expr` or in case of a failure an object of class `fail`, which contains the error message.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_body\(\)](#), [function_defaults\(\)](#), [quiet\(\)](#), [timed\(\)](#), [variable_name\(\)](#)

Examples

```
## Not run:  
try_silent(1 + 1)  
try_silent(1 + "1")  
  
## End(Not run)
```

unexpected_error	<i>Handling of an unexpected error</i>
------------------	--

Description

This function reacts to an unexpected error by throwing an error and linking to an issue site with the request to submit an issue.

Usage

```
unexpected_error(  
  msg = "Ups, an unexpected error occurred.",  
  issue_link = "https://github.com/loelschlaeger/oeli/issues"  
)
```

Arguments

msg	[character(1)] An error message.
issue_link	[character(1)] The URL to an issues site.

Value

No return value, but it throws an error.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [user_confirm\(\)](#)

user_confirm	<i>User confirmation</i>
--------------	--------------------------

Description

This function asks in an interactive question a binary question.

Usage

```
user_confirm(question = "Question?", default = FALSE)
```

Arguments

question	[character(1)] The binary question to ask. It should end with a question mark.
default	[logical(1)] The default decision.

Value

Either TRUE or FALSE.

See Also

Other package helpers: [Dictionary](#), [Storage](#), [check_missing\(\)](#), [find_namespace_calls\(\)](#), [identical_structure\(\)](#), [input_check_response\(\)](#), [match_arg\(\)](#), [package_logo\(\)](#), [print_data.frame\(\)](#), [print_matrix\(\)](#), [system_information\(\)](#), [unexpected_error\(\)](#)

variable_name	<i>Determine variable name</i>
---------------	--------------------------------

Description

This function tries to determine the name of a variable passed to a function.

Usage

```
variable_name(variable, fallback = "unnamed")
```

Arguments

variable	[any] Any object.
fallback	[character(1)] A fallback name if for some reason the actual variable name (which must be a single character) cannot be determined.

Value

A character, the variable name.

See Also

Other function helpers: [do.call_timed\(\)](#), [function_arguments\(\)](#), [function_body\(\)](#), [function_defaults\(\)](#), [quiet\(\)](#), [timed\(\)](#), [try_silent\(\)](#)

Examples

```
variable_name(a)
f <- function(x) variable_name(x)
f(x = a)
```

vector_occurrence	<i>Find the positions of first or last occurrence of unique vector elements</i>
-------------------	---

Description

This function finds the positions of first or last occurrence of unique vector elements.

Usage

```
vector_occurrence(x, type = "first")
```

Arguments

x	[atomic()] A vector.
type	[character(1)] Either "first" for the first or "last" for the last occurrence.

Value

An integer vector, the positions of the unique vector elements. The ordering corresponds to `unique(x)`, i.e., the i -th element in the output is the (first or last) occurrence of the i -th element from `unique(x)`.

See Also

Other vector helpers: [check_numeric_vector\(\)](#), [check_probability_vector\(\)](#), [chunk_vector\(\)](#), [insert_vector_entry\(\)](#), [map_indices\(\)](#), [match_numerics\(\)](#), [permutations\(\)](#), [split_vector_at\(\)](#), [subsets\(\)](#)

Examples

```
x <- c(1, 1, 1, 2, 2, 2, 3, 3, 3)
unique(x)
vector_occurrence(x, "first")
vector_occurrence(x, "last")
```

Index

- * **data.frame helpers**
 - delete_columns_data.frame, [17](#)
 - group_data.frame, [31](#)
 - round_data.frame, [47](#)
- * **distribution**
 - ddirichlet_cpp, [16](#)
 - dmvnorm_cpp, [23](#)
 - dtnorm_cpp, [25](#)
 - dwishart_cpp, [26](#)
- * **function helpers**
 - do.call_timed, [24](#)
 - function_arguments, [29](#)
 - function_body, [29](#)
 - function_defaults, [30](#)
 - quiet, [46](#)
 - timed, [59](#)
 - try_silent, [60](#)
 - variable_name, [62](#)
- * **functional**
 - function_arguments, [29](#)
 - function_body, [29](#)
 - function_defaults, [30](#)
 - quiet, [46](#)
 - try_silent, [60](#)
 - variable_name, [62](#)
- * **indexing**
 - Dictionary, [18](#)
 - map_indices, [36](#)
 - match_numerics, [38](#)
 - matrix_diagonal_indices, [39](#)
 - matrix_indices, [40](#)
 - permutations, [43](#)
 - Storage, [53](#)
 - subsets, [57](#)
 - vector_occurrence, [63](#)
- * **list helpers**
 - check_list_of_lists, [5](#)
 - merge_lists, [41](#)
- * **matrix helpers**
 - check_correlation_matrix, [3](#)
 - check_covariance_matrix, [4](#)
 - check_transition_probability_matrix, [11](#)
 - cov_to_chol, [15](#)
 - diff_cov, [21](#)
 - insert_matrix_column, [34](#)
 - matrix_diagonal_indices, [39](#)
 - matrix_indices, [40](#)
 - sample_correlation_matrix, [48](#)
 - sample_covariance_matrix, [49](#)
 - sample_transition_probability_matrix, [50](#)
 - stationary_distribution, [52](#)
- * **package helpers**
 - check_missing, [6](#)
 - Dictionary, [18](#)
 - find_namespace_calls, [28](#)
 - identical_structure, [32](#)
 - input_check_response, [33](#)
 - match_arg, [37](#)
 - package_logo, [41](#)
 - print_data.frame, [43](#)
 - print_matrix, [45](#)
 - Storage, [53](#)
 - system_information, [58](#)
 - unexpected_error, [61](#)
 - user_confirm, [61](#)
- * **packaging**
 - find_namespace_calls, [28](#)
 - input_check_response, [33](#)
 - match_arg, [37](#)
 - package_logo, [41](#)
 - print_data.frame, [43](#)
 - print_matrix, [45](#)
 - unexpected_error, [61](#)
- * **simulation helpers**
 - correlated_regressors, [13](#)
 - ddirichlet_cpp, [16](#)

- dmvnorm_cpp, 23
- dtnorm_cpp, 25
- dwishart_cpp, 26
- simulate_markov_chain, 50
- * **simulation**
 - correlated_regressors, 13
 - do.call_timed, 24
 - sample_correlation_matrix, 48
 - sample_covariance_matrix, 49
 - sample_transition_probability_matrix, 50
 - simulate_markov_chain, 50
 - timed, 59
- * **transformation**
 - chunk_vector, 12
 - cov_to_chol, 15
 - delete_columns_data.frame, 17
 - diff_cov, 21
 - group_data.frame, 31
 - insert_matrix_column, 34
 - insert_vector_entry, 35
 - merge_lists, 41
 - round_data.frame, 47
 - split_vector_at, 51
 - stationary_distribution, 52
- * **validation**
 - check_correlation_matrix, 3
 - check_covariance_matrix, 4
 - check_list_of_lists, 5
 - check_missing, 6
 - check_numeric_vector, 7
 - check_probability_vector, 10
 - check_transition_probability_matrix, 11
 - identical_structure, 32
 - system_information, 58
 - user_confirm, 61
- * **vector helpers**
 - check_numeric_vector, 7
 - check_probability_vector, 10
 - chunk_vector, 12
 - insert_vector_entry, 35
 - map_indices, 36
 - match_numerics, 38
 - permutations, 43
 - split_vector_at, 51
 - subsets, 57
 - vector_occurrence, 63
- assert_correlation_matrix
 - (check_correlation_matrix), 3
- assert_covariance_matrix
 - (check_covariance_matrix), 4
- assert_list_of_lists
 - (check_list_of_lists), 5
- assert_missing(check_missing), 6
- assert_numeric_vector
 - (check_numeric_vector), 7
- assert_probability_vector
 - (check_probability_vector), 10
- assert_transition_probability_matrix
 - (check_transition_probability_matrix), 11
- AssertCollection, 3, 5, 6, 9, 10, 12
- check_correlation_matrix, 3, 5, 12, 15, 22, 35, 39, 40, 48–50, 52
- check_covariance_matrix, 4, 4, 12, 15, 22, 35, 39, 40, 48–50, 52
- check_list, 6
- check_list_of_lists, 5, 41
- check_matrix, 3, 5, 12
- check_missing, 6, 20, 28, 32, 33, 38, 42, 44, 46, 57, 58, 61, 62
- check_numeric, 9, 11
- check_numeric_vector, 7, 11, 13, 36, 37, 39, 43, 52, 58, 63
- check_probability_vector, 9, 10, 13, 36, 37, 39, 43, 52, 58, 63
- check_transition_probability_matrix, 4, 5, 11, 15, 22, 35, 39, 40, 48–50, 52
- checkNamed, 9
- checkSubset, 9
- chol_to_cov, 15
- chol_to_cov(cov_to_chol), 15
- chunk_vector, 9, 11, 12, 36, 37, 39, 43, 52, 58, 63
- class, 32
- correlated_regressors, 13, 16, 24, 26, 27, 51
- cov_to_chol, 4, 5, 12, 15, 15, 22, 35, 39, 40, 48–50, 52
- ddirichlet(ddirichlet_cpp), 16
- ddirichlet_cpp, 14, 16, 24, 26, 27, 51
- delete_columns_data.frame, 17, 31, 47
- delta(diff_cov), 21

- Dictionary, [7](#), [18](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- diff_cov, [4](#), [5](#), [12](#), [15](#), [21](#), [35](#), [39](#), [40](#), [48–50](#), [52](#)
- difftime, [24](#)
- dmvnorm (dmvnorm_cpp), [23](#)
- dmvnorm_cpp, [14](#), [16](#), [23](#), [26](#), [27](#), [51](#)
- do.call, [24](#)
- do.call_timed, [24](#), [29–31](#), [47](#), [59](#), [60](#), [62](#)
- dtnorm (dtnorm_cpp), [25](#)
- dtnorm_cpp, [14](#), [16](#), [24](#), [25](#), [27](#), [51](#)
- dttnorm (dttnorm_cpp), [25](#)
- dttnorm_cpp (dtnorm_cpp), [25](#)
- dwishart (dwishart_cpp), [26](#)
- dwishart_cpp, [14](#), [16](#), [24](#), [26](#), [26](#), [51](#)
- find_namespace_calls, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- function_arguments, [25](#), [29](#), [30](#), [31](#), [47](#), [59](#), [60](#), [62](#)
- function_body, [25](#), [29](#), [29](#), [31](#), [47](#), [59](#), [60](#), [62](#)
- function_defaults, [25](#), [29](#), [30](#), [30](#), [47](#), [59](#), [60](#), [62](#)
- group_data.frame, [17](#), [31](#), [47](#)
- identical_structure, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- input_check_response, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- insert_matrix_column, [4](#), [5](#), [12](#), [15](#), [22](#), [34](#), [39](#), [40](#), [48–50](#), [52](#)
- insert_vector_entry, [9](#), [11](#), [13](#), [35](#), [37](#), [39](#), [43](#), [52](#), [58](#), [63](#)
- M(diff_cov), [21](#)
- map_indices, [9](#), [11](#), [13](#), [36](#), [36](#), [39](#), [43](#), [52](#), [58](#), [63](#)
- match.arg, [37](#)
- match_arg, [7](#), [20](#), [28](#), [32](#), [33](#), [37](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- match_numerics, [9](#), [11](#), [13](#), [36](#), [37](#), [38](#), [43](#), [52](#), [58](#), [63](#)
- matrix_diagonal_indices, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48–50](#), [52](#)
- matrix_indices, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48–50](#), [52](#)
- merge_lists, [6](#), [41](#)
- mode, [32](#)
- package_logo, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [41](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- permutations, [9](#), [11](#), [13](#), [36](#), [37](#), [39](#), [43](#), [52](#), [58](#), [63](#)
- print_data.frame, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [43](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- print_matrix, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [45](#), [57](#), [58](#), [61](#), [62](#)
- quiet, [25](#), [29–31](#), [46](#), [46](#), [59](#), [60](#), [62](#)
- rdirichlet (ddirichlet_cpp), [16](#)
- rdirichlet_cpp (ddirichlet_cpp), [16](#)
- rmvnorm (dmvnorm_cpp), [23](#)
- rmvnorm_cpp (dmvnorm_cpp), [23](#)
- round_data.frame, [17](#), [31](#), [47](#)
- rttnorm (dtnorm_cpp), [25](#)
- rttnorm_cpp (dtnorm_cpp), [25](#)
- rttnorm (dtnorm_cpp), [25](#)
- rttnorm_cpp (dtnorm_cpp), [25](#)
- rwishart (dwishart_cpp), [26](#)
- rwishart_cpp (dwishart_cpp), [26](#)
- sample_correlation_matrix, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48](#), [49](#), [50](#), [52](#)
- sample_covariance_matrix, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48](#), [49](#), [50](#), [52](#)
- sample_transition_probability_matrix, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48](#), [49](#), [50](#), [52](#)
- setTimeLimit, [59](#)
- simulate_markov_chain, [14](#), [16](#), [24](#), [26](#), [27](#), [50](#)
- split_vector_at, [9](#), [11](#), [13](#), [36](#), [37](#), [39](#), [43](#), [51](#), [58](#), [63](#)
- stationary_distribution, [4](#), [5](#), [12](#), [15](#), [22](#), [35](#), [39](#), [40](#), [48–50](#), [52](#)
- sticker, [42](#)
- Storage, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [53](#), [58](#), [61](#), [62](#)
- subsets, [9](#), [11](#), [13](#), [36](#), [37](#), [39](#), [43](#), [52](#), [57](#), [63](#)
- system_information, [7](#), [20](#), [28](#), [32](#), [33](#), [38](#), [42](#), [44](#), [46](#), [57](#), [58](#), [61](#), [62](#)
- test_correlation_matrix (check_correlation_matrix), [3](#)
- test_covariance_matrix (check_covariance_matrix), [4](#)
- test_list_of_lists (check_list_of_lists), [5](#)

`test_missing`(`check_missing`), 6
`test_numeric_vector`
 (`check_numeric_vector`), 7
`test_probability_vector`
 (`check_probability_vector`), 10
`test_transition_probability_matrix`
 (`check_transition_probability_matrix`),
 11
`timed`, 25, 29–31, 47, 59, 60, 62
`try`, 60
`try_silent`, 25, 29–31, 47, 59, 60, 62

`undiff_cov`(`diff_cov`), 21
`unexpected_error`, 7, 20, 28, 32, 33, 38, 42,
 44, 46, 57, 58, 61, 62
`unique_chol`(`cov_to_chol`), 15
`use_logo`, 42
`user_confirm`, 7, 20, 28, 32, 33, 38, 42, 44,
 46, 57, 58, 61, 61

`variable_name`, 25, 29–31, 47, 59, 60, 62
`vector_occurrence`, 9, 11, 13, 36, 37, 39, 43,
 52, 58, 63
`vname`, 3, 5, 6, 9, 10, 12